

Δ Tandem Controller Required

* Range is limited by power source rating, module rating, or feeder configuration

Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)	
All	All	GMAW CV	STD CV		5	Pinch	10 – 55	V
		GMAW Power	Power Mode®		40	Pinch	0.1 – 40	kW
		GMAW Power	Process HDT® ¹		635	Pinch	0.1 – 40	kW
Steel	0.030	GMAW CV	CV	CO ₂	93	Pinch	75 – 1200	ipm (1.91 – 30.48 m/min)
			Argon Mix	94	75 – 1200		ipm (1.91 – 30.48 m/min)	
		GMAW Pulse	Pulse	Argon Mix	95	UltimArc®	65 – 1200	ipm (1.65 – 30.48 m/min)
	0.035	GMAW CV	CV	CO ₂	10	Pinch	50 – 1200	ipm (1.27 – 30.48 m/min)
			Argon Mix	11	50 – 1200		ipm (1.27 – 30.48 m/min)	
		GMAW Pulse	Pulse	Argon Mix	12	UltimArc®	60 – 1200	ipm (1.52 – 30.48 m/min)
			RapidArc®	Argon Mix	13		60 – 1200	ipm (1.52 – 30.48 m/min)
			Precision Pulse™	Argon Mix	411		100 – 600	ipm (2.54 – 15.24 m/min)
	0.040	GMAW CV	CV	CO ₂	138	Pinch	50 – 1200	ipm (1.27 – 30.48 m/min)
			Argon Mix	139	50 – 1200		ipm (1.27 – 30.48 m/min)	
		GMAW Pulse	Pulse	Argon Mix	140	UltimArc®	60 – 1200	ipm (1.52 – 30.48 m/min)
			RapidArc®	Argon Mix	141		60 – 1200	ipm (1.52 – 30.48 m/min)
			Precision Pulse™	Argon Mix	412		75 – 600	ipm (1.91 – 15.24 m/min)
	0.045	GMAW CV	CV	CO ₂	20	Pinch	50 – 800	ipm (1.27 – 20.32 m/min)
			Argon Mix	21	50 – 800		ipm (1.27 – 20.32 m/min)	
		GMAW Pulse	Pulse	Argon Mix	22	UltimArc®	50 – 800	ipm (1.27 – 20.32 m/min)
			RapidArc®	Argon Mix	18		75 – 800	ipm (1.91 – 20.32 m/min)
			Precision Pulse™	Argon Mix	413		75 – 600	ipm (1.91 – 15.24 m/min)
	0.052	GMAW CV	CV	CO ₂	24	Pinch	50 – 750	ipm (1.27 – 19.05 m/min)
			Argon Mix	25	50 – 700		ipm (1.27 – 17.78 m/min)	
		GMAW Pulse	Pulse	Argon Mix	26	UltimArc®	50 – 700	ipm (1.27 – 17.78 m/min)
			RapidArc®	Argon Mix	27		60 – 750	ipm (1.52 – 19.05 m/min)
			Precision Pulse™	Argon Mix	414		75 – 500	ipm (1.91 – 12.7 m/min)
	1/16	GMAW CV	CV	Argon Mix	107	Pinch	50 – 700	ipm (1.27 – 17.78 m/min)
GMAW Pulse		Pulse	Argon Mix	108	UltimArc®	50 – 500	ipm (1.27 – 12.7 m/min)	
Stainless	0.030	GMAW CV	CV	Argon Mix	61	Pinch	100 – 1200	ipm (2.54 – 30.48 m/min)
			He Ar CO ₂	63	100 – 1200		ipm (2.54 – 30.48 m/min)	
		GMAW Pulse	Pulse	He Ar CO ₂	64	UltimArc®	90 – 1200	ipm (2.29 – 30.48 m/min)
			Argon Mix	66	80 – 1200		ipm (2.03 – 30.48 m/min)	
			Precision Pulse™	Argon Mix	420		100 – 800	ipm (2.54 – 20.32 m/min)
			He Ar CO ₂	430		100 – 800	ipm (2.54 – 20.32 m/min)	
	0.035	GMAW CV	CV	Argon Mix	31	Pinch	75 – 1200	ipm (1.91 – 30.48 m/min)
			He Ar CO ₂	33	75 – 1200		ipm (1.91 – 30.48 m/min)	
		GMAW Pulse	Pulse	He Ar CO ₂	34	UltimArc®	75 – 1200	ipm (1.91 – 30.48 m/min)
			Argon Mix	36	60 – 1200		ipm (1.52 – 30.48 m/min)	
			Precision Pulse™	Argon Mix	421		100 – 600	ipm (2.54 – 15.24 m/min)
			He Ar CO ₂	431		100 – 700	ipm (2.54 – 17.78 m/min)	
	0.045	GMAW CV	CV	Argon Mix	41	Pinch	75 – 800	ipm (1.91 – 20.32 m/min)
			He Ar CO ₂	43	75 – 800		ipm (1.91 – 20.32 m/min)	
		GMAW Pulse	Pulse	He Ar CO ₂	44	UltimArc®	75 – 800	ipm (1.91 – 20.32 m/min)
			Argon Mix	46	50 – 800		ipm (1.27 – 20.32 m/min)	
			Precision Pulse™	Argon Mix	423		50 – 400	ipm (1.27 – 10.16 m/min)
			He Ar CO ₂	433		60 – 400	ipm (1.52 – 10.16 m/min)	
1/16	GMAW CV	CV	Argon Mix	51	Pinch	50 – 600	ipm (1.27 – 15.24 m/min)	
	GMAW Pulse	Pulse	Argon Mix	56	UltimArc®	50 – 700	ipm (1.27 – 17.78 m/min)	
Metal Core	0.045	GMAW CV	CV	Argon Mix	81	Pinch	100 – 700	ipm (2.54 – 17.78 m/min)
			GMAW Pulse	Pulse	Argon Mix		82	50 – 700
			RapidArc®	Argon Mix	87	UltimArc®	75 – 800	ipm (1.91 – 20.32 m/min)
	0.052	GMAW CV	CV	Argon Mix	83	Pinch	50 – 600	ipm (1.27 – 15.24 m/min)
			GMAW Pulse	Pulse	Argon Mix		84	50 – 600
			RapidArc®	Argon Mix	88	UltimArc®	60 – 800	ipm (1.52 – 20.32 m/min)
	1/16	GMAW CV	CV	Argon Mix	85	Pinch	50 – 450	ipm (1.27 – 11.43 m/min)
GMAW Pulse		Pulse	Argon Mix	86	UltimArc®	50 – 450	ipm (1.27 – 11.43 m/min)	
		RapidArc®	Argon Mix	89		60 – 450	ipm (1.52 – 11.43 m/min)	

Δ Tandem Controller Required

* Range is limited by power source rating, module rating, or feeder configuration

GMAW	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)		
	Aluminum 4XXX	0.035	GMAW CV	CV	Argon	148	Pinch	150 – 750	ipm	(3.81 – 19.05 m/min)
Pulse				Argon	149	UltimArc®	125 – 800	ipm	(3.18 – 20.32 m/min)	
CC Pulse				Argon	150		125 – 800	ipm	(3.18 – 20.32 m/min)	
Precision Pulse®				Argon	565	125 – 800	ipm	(3.18 – 20.32 m/min)		
GMAW Pulse on Pulse®			Pulse on Pulse®	Argon	98	Frequency	125 – 800	ipm	(3.18 – 20.32 m/min)	
3/64			GMAW CV	CV	Argon	71	Pinch	125 – 700	ipm	(3.18 – 17.78 m/min)
				Pulse	Argon	72	UltimArc®	85 – 600	ipm	(2.16 – 15.24 m/min)
				CC Pulse	Argon	69		85 – 600	ipm	(2.16 – 15.24 m/min)
				Precision Pulse®	Argon	567	85 – 600	ipm	(2.16 – 15.24 m/min)	
GMAW Pulse on Pulse®			Pulse on Pulse®	Argon	99	Frequency	85 – 500	ipm	(2.16 – 12.7 m/min)	
1/16			GMAW CV	CV	Argon	73	Pinch	75 – 375	ipm	(1.91 – 9.53 m/min)
				Pulse	Argon	74	UltimArc®	75 – 350	ipm	(1.91 – 8.89 m/min)
		CC Pulse		Argon	79	75 – 350		ipm	(1.91 – 8.89 m/min)	
		Precision Pulse®		Argon	568	75 – 350	ipm	(1.91 – 8.89 m/min)		
GMAW Pulse on Pulse®		Pulse on Pulse®	Argon	100	Frequency	80 – 400	ipm	(2.03 – 10.16 m/min)		
Aluminum 5XXX		0.035	GMAW CV	CV	Argon	151	Pinch	175 – 750	ipm	(4.45 – 19.05 m/min)
				Pulse	Argon	152	UltimArc®	150 – 800	ipm	(3.81 – 20.32 m/min)
				CC Pulse	Argon	153		150 – 800	ipm	(3.81 – 20.32 m/min)
				Precision Pulse®	Argon	570	150 – 800	ipm	(3.81 – 20.32 m/min)	
		GMAW Pulse on Pulse®	Pulse on Pulse®	Argon	101	Frequency	140 – 800	ipm	(3.56 – 20.32 m/min)	
		3/64	GMAW CV	CV	Argon	75	Pinch	125 – 750	ipm	(3.18 – 19.05 m/min)
				Pulse	Argon	76	UltimArc®	85 – 700	ipm	(2.16 – 17.78 m/min)
				CC Pulse	Argon	70		85 – 700	ipm	(2.16 – 17.78 m/min)
				Precision Pulse®	Argon	572	85 – 700	ipm	(2.16 – 17.78 m/min)	
	GMAW Pulse on Pulse®	Pulse on Pulse®	Argon	102	Frequency	100 – 600	ipm	(2.54 – 15.24 m/min)		
	1/16	GMAW CV	CV	Argon	77	Pinch	125 – 500	ipm	(3.18 – 12.7 m/min)	
			Pulse	Argon	78	UltimArc®	100 – 500	ipm	(2.54 – 12.7 m/min)	
CC Pulse			Argon	80	100 – 450		ipm	(2.54 – 11.43 m/min)		
Precision Pulse®			Argon	573	100 – 400	ipm	(2.54 – 10.16 m/min)			
GMAW Pulse on Pulse®	Pulse on Pulse®	Argon	103	Frequency	75 – 350	ipm	(1.91 – 8.89 m/min)			
SiBr	0.035	GMAW Pulse	Pulse	Argon	192	UltimArc®	80 – 1200	ipm	(2.03 – 30.48 m/min)	
	0.045	GMAW Pulse	Pulse	Argon	191	UltimArc®	50 – 600	ipm	(1.27 – 15.24 m/min)	
Cu	0.035	GMAW Pulse	Pulse	Argon Helium	198	UltimArc®	100 – 700	ipm	(2.54 – 17.78 m/min)	
	0.045	GMAW Pulse	Pulse	Argon Helium	196	UltimArc®	75 – 500	ipm	(1.91 – 12.7 m/min)	
NiCr	0.035	GMAW Pulse	Pulse	Ar/ Ar He	501	UltimArc®	75 – 800	ipm	(1.91 – 20.32 m/min)	
	0.045	GMAW Pulse	Pulse	Ar/ Ar He	503	UltimArc®	75 – 600	ipm	(1.91 – 15.24 m/min)	
	1/16	GMAW Pulse	Pulse	Ar/ Ar He	505	UltimArc®	75 – 350	ipm	(1.91 – 8.89 m/min)	
NiCu	0.035	GMAW Pulse	Pulse	Ar/ Ar He	507	UltimArc®	75 – 800	ipm	(1.91 – 20.32 m/min)	
	0.045	GMAW Pulse	Pulse	Ar/ Ar He	509	UltimArc®	75 – 600	ipm	(1.91 – 15.24 m/min)	
	1/16	GMAW Pulse	Pulse	Ar/ Ar He	511	UltimArc®	50 – 350	ipm	(1.27 – 8.89 m/min)	
NiFe-CI	0.035	GMAW Pulse	Pulse	Ar/ Ar He	513	UltimArc®	75 – 800	ipm	(1.91 – 20.32 m/min)	
	0.045	GMAW Pulse	Pulse	Ar/ Ar He	515	UltimArc®	75 – 600	ipm	(1.91 – 15.24 m/min)	
Ni-1	0.035	GMAW Pulse	Pulse	Ar/ Ar He	519	UltimArc®	75 – 800	ipm	(1.91 – 20.32 m/min)	
	0.045	GMAW Pulse	Pulse	Ar/ Ar He	521	UltimArc®	75 – 600	ipm	(1.91 – 15.24 m/min)	
	1/16	GMAW Pulse	Pulse	Ar/ Ar He	523	UltimArc®	50 – 300	ipm	(1.27 – 7.62 m/min)	
Ni-CI	0.035	GMAW Pulse	Pulse	Ar/ Ar He	525	UltimArc®	75 – 800	ipm	(1.91 – 20.32 m/min)	
	0.045	GMAW Pulse	Pulse	Ar/ Ar He	527	UltimArc®	75 – 500	ipm	(1.91 – 12.7 m/min)	

FCAW	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)	
	Flux Core	All	FCAW-S	Self Shield CV	NA	6	Pinch	10 – 45	V
FCAW-G			Gas Shield CV	NA	7	Pinch	10 – 45	V	
Cored Wire	0.045	FCAW-G	CV	CO ₂	90	Pinch	175 – 600	ipm	(4.45 – 15.24 m/min)
			Argon Mix	91	175 – 600		ipm	(4.45 – 15.24 m/min)	
	0.052	FCAW-G	CV	CO ₂	187	Pinch	150 – 500	ipm	(3.81 – 12.7 m/min)
			Argon Mix	188	150 – 500		ipm	(3.81 – 12.7 m/min)	
1/16	FCAW-G	CV	CO ₂	189	Pinch	125 – 400	ipm	(3.18 – 10.16 m/min)	
		Argon Mix	190	125 – 400		ipm	(3.18 – 10.16 m/min)		

SMAW	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)		
	NA	NA	DCEP SMAW	SMAW Soft	NA	1	Arc Force, Hot Start	15 – 900	A	
				SMAW Crisp	NA	2	Arc Force, Hot Start	15 – 900	A	
				SMAW Pipe	NA	4	Arc Force	50 – 250	A	

Δ Tandem Controller Required

* Range is limited by power source rating, module rating, or feeder configuration

GTAW	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)
	NA	NA	DCEN GTAW	Touch Start TIG	Ar / He	3	Hot Start	5 – 900 A
			Touch Start TIG Pulse	Ar / He	8	Frequency, Background, Hot Start	5 – 800 A	

CAG	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)
	NA	NA	CAG	Arc Gouge	Compressed Air	9		60 – 900 A

GMAW-Tandem	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)
	Steel	0.035	GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	400	UltimArc®, Phase Angle	100 – 1000 ipm (2.54 – 25.4 m/min)
Sync Pulse Trail				Argon Mix	401	UltimArc®	100 – 800 ipm (2.54 – 20.32 m/min)	
HotWire Pulse Trail				Argon Mix	460		80 – 900 ipm (2.03 – 22.86 m/min)	
0.040		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	402	UltimArc®, Phase Angle	150 – 800 ipm (3.81 – 20.32 m/min)	
			Sync Pulse Trail	Argon Mix	403	UltimArc®	150 – 800 ipm (3.81 – 20.32 m/min)	
			HotWire Pulse Trail	Argon Mix	461		80 – 800 ipm (2.03 – 20.32 m/min)	
0.045		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	404	UltimArc®, Phase Angle	100 – 700 ipm (2.54 – 17.78 m/min)	
			Sync Pulse Trail	Argon Mix	405	UltimArc®	100 – 700 ipm (2.54 – 17.78 m/min)	
			HotWire Pulse Trail	Argon Mix	462		75 – 800 ipm (1.91 – 20.32 m/min)	
0.052		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	406	UltimArc®, Phase Angle	100 – 800 ipm (2.54 – 20.32 m/min)	
			Sync Pulse Trail	Argon Mix	407	UltimArc®	100 – 800 ipm (2.54 – 20.32 m/min)	
			HotWire Pulse Trail	Argon Mix	463		50 – 800 ipm (1.27 – 20.32 m/min)	
1/16		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	408	UltimArc®, Phase Angle	100 – 500 ipm (2.54 – 12.7 m/min)	
			Sync Pulse Trail	Argon Mix	409	UltimArc®	100 – 500 ipm (2.54 – 12.7 m/min)	
			HotWire Pulse Trail	Argon Mix	464		50 – 500 ipm (1.27 – 12.7 m/min)	

GMAW- HyperFill ¹	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)
	Steel	0.035	GMAW	HyperFill	Argon Mix	601		100 – 800 ipm (2.54 – 20.32 m/min)
		0.040	GMAW	HyperFill	Argon Mix	602		100 – 600 ipm (2.54 – 15.24 m/min)
		0.045	GMAW	HyperFill	Argon Mix	603		100 – 465 ipm (2.54 – 11.81 m/min)
	Metal Core	0.045	GMAW	HyperFill	Argon Mix	608		100 – 515 ipm (2.54 – 13.08 m/min)
FCAW-G	0.045	GMAW	HyperFill	Argon Mix	618		100 – 430 ipm (2.54 – 10.92 m/min)	

GTAW - APEX ²	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)
	NA	NA	DCEN GTAW	Touch Start TIG	NA	490	Transition Speed	5 – 500 A

¹HyperFill® & Process HDT™ Waveform Activation Capability with Power Wave® and PIPEFAB™ Systems

Your purchase of a Lincoln Power Wave or PIPEFAB Welding System comes with (i) a license to use Lincoln Electric standard Power Wave / PIPEFAB waveforms, and (ii) HyperFill & Process HDT waveform capability, which requires a separate license. Without the separate license, the HyperFill and Process HDT waveforms are not available for use on these machines, and only the standard Power Wave / PIPEFAB waveforms are usable.

²APEX® System Required