

□ HyperFill Key Required

◆ HDT Key Required

△ Tandem Controller Required

* Range is limited by power source rating, module rating, or feeder configuration

	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)			
	All	All		GMAW CV	STD CV		5	Pinch	10 — 55	V	
			GMAW Power	Power Mode®		40	Pinch	0.1 — 40	kW		
			GMAW Power	Process HDT® ¹		635	Pinch	0.1 — 40	kW		
GMAW	Steel	0.8 mm	GMAW CV	CV	CO ₂	93	Pinch	75 — 1200	ipm (1.91 — 30.48 m/min)		
					Argon Mix	94		75 — 1200	ipm (1.91 — 30.48 m/min)		
			GMAW Pulse	Pulse	Argon Mix	95	UltimArc®	65 — 1200	ipm (1.65 — 30.48 m/min)		
				Precision Pulse™	Argon Mix	410		100 — 600	ipm (2.54 — 15.24 m/min)		
		0.9 mm	GMAW CV	CV	CO ₂	138	Pinch	50 — 1200	ipm (1.27 — 30.48 m/min)		
					Argon Mix	139		50 — 1200	ipm (1.27 — 30.48 m/min)		
				GMAW Pulse	Pulse	Argon Mix		140	UltimArc®	60 — 1200	ipm (1.52 — 30.48 m/min)
		RapidArc®	Argon Mix		141	75 — 1200	ipm (1.91 — 30.48 m/min)				
				Precision Pulse™	Argon Mix	411		100 — 600	ipm (2.54 — 15.24 m/min)		
		1.0 mm	GMAW CV	CV	CO ₂	10	Pinch	50 — 1200	ipm (1.27 — 30.48 m/min)		
					Argon Mix	11		50 — 1200	ipm (1.27 — 30.48 m/min)		
				GMAW Pulse	Pulse	Argon Mix		12	UltimArc®	75 — 1200	ipm (1.91 — 30.48 m/min)
					RapidArc®	Argon Mix		13		60 — 1200	ipm (1.52 — 30.48 m/min)
				Precision Pulse™	Argon Mix	412		75 — 600	ipm (1.91 — 15.24 m/min)		
		1.2 mm	GMAW CV	CV	CO ₂	20	Pinch	50 — 800	ipm (1.27 — 20.32 m/min)		
					Argon Mix	21		50 — 800	ipm (1.27 — 20.32 m/min)		
				GMAW Pulse	Pulse	Argon Mix		22	UltimArc®	60 — 800	ipm (1.52 — 20.32 m/min)
					RapidArc®	Argon Mix		18		60 — 800	ipm (1.52 — 20.32 m/min)
				Precision Pulse™	Argon Mix	413		75 — 600	ipm (1.91 — 15.24 m/min)		
		1.32 mm	GMAW CV	CV	Argon Mix	540	Pinch	50 — 550	ipm (1.27 — 13.97 m/min)		
					Argon Mix	541		60 — 1000	ipm (1.52 — 25.4 m/min)		
		1.4 mm	GMAW CV	CV	CO ₂	24	Pinch	50 — 650	ipm (1.27 — 16.51 m/min)		
					Argon Mix	25		50 — 550	ipm (1.27 — 13.97 m/min)		
				GMAW Pulse	Pulse	Argon Mix		26	UltimArc®	50 — 600	ipm (1.27 — 15.24 m/min)
RapidArc®	Argon Mix				27	60 — 1000		ipm (1.52 — 25.4 m/min)			
1.6 mm	GMAW CV	CV	Argon Mix	107	Pinch	50 — 350	ipm (1.27 — 8.89 m/min)				
			Argon Mix	108		50 — 400	ipm (1.27 — 10.16 m/min)				
1.6 mm	GMAW Pulse	Pulse	Argon Mix	108	UltimArc®	50 — 400	ipm (1.27 — 10.16 m/min)				
			Argon Mix	108		50 — 400	ipm (1.27 — 10.16 m/min)				
GMAW	Stainless	0.8 mm	GMAW CV	CV	Argon Mix	61	Pinch	100 — 1200	ipm (2.54 — 30.48 m/min)		
					Ar He CO ₂	63		100 — 1200	ipm (2.54 — 30.48 m/min)		
				GMAW Pulse	Pulse	Ar He CO ₂		64	UltimArc®	100 — 1200	ipm (2.54 — 30.48 m/min)
						Argon Mix		66		100 — 1200	ipm (2.54 — 30.48 m/min)
		0.9 mm	GMAW CV	CV	Argon Mix	29	Pinch	75 — 1200	ipm (1.91 — 30.48 m/min)		
					Argon Mix	30		60 — 1200	ipm (1.52 — 30.48 m/min)		
				GMAW Pulse	Precision Pulse™	Argon Mix		421	100 — 600	ipm (2.54 — 15.24 m/min)	
		1.0 mm	GMAW CV	CV	Argon Mix	31	Pinch	75 — 1200	ipm (1.91 — 30.48 m/min)		
					Ar He CO ₂	33		75 — 1000	ipm (1.91 — 25.4 m/min)		
				GMAW Pulse	Pulse	Ar He CO ₂		34	UltimArc®	60 — 1200	ipm (1.52 — 30.48 m/min)
						Argon Mix		36		60 — 1200	ipm (1.52 — 30.48 m/min)
				Precision Pulse™	Argon Mix	422	UltimArc®	60 — 600	ipm (1.52 — 15.24 m/min)		
		1.2 mm	GMAW CV	CV	Argon Mix	41	Pinch	75 — 700	ipm (1.91 — 17.78 m/min)		
					Ar He CO ₂	43		75 — 700	ipm (1.91 — 17.78 m/min)		
				GMAW Pulse	Pulse	Ar He CO ₂		44	UltimArc®	50 — 700	ipm (1.27 — 17.78 m/min)
						Argon Mix		46		50 — 800	ipm (1.27 — 20.32 m/min)
				Precision Pulse™	Argon Mix	423	UltimArc®	50 — 400	ipm (1.27 — 10.16 m/min)		
		1.6 mm	GMAW CV	CV	Argon Mix	51	Pinch	50 — 600	ipm (1.27 — 15.24 m/min)		
					Argon Mix	56		50 — 700	ipm (1.27 — 17.78 m/min)		
		1.6 mm	GMAW Pulse	Pulse	Argon Mix	56	UltimArc®	50 — 700	ipm (1.27 — 17.78 m/min)		
					Argon Mix	56		50 — 700	ipm (1.27 — 17.78 m/min)		
		GMAW	Metal Core	1.2 mm	GMAW CV	CV	Argon Mix	81	Pinch	50 — 700	ipm (1.27 — 17.78 m/min)
							Argon Mix	82		50 — 700	ipm (1.27 — 17.78 m/min)
				1.4 mm	GMAW CV	CV	CO ₂	252	Pinch	100 — 1200	ipm (2.54 — 30.48 m/min)
	Argon Mix					83	50 — 1200	ipm (1.27 — 30.48 m/min)			
1.6 mm	GMAW Pulse			Pulse	Argon Mix	84	UltimArc®	50 — 600	ipm (1.27 — 15.24 m/min)		
					RapidArc®	Argon Mix		88	60 — 1000	ipm (1.52 — 25.4 m/min)	
1.6 mm	GMAW CV	CV	Argon Mix	85	Pinch	50 — 450	ipm (1.27 — 11.43 m/min)				
			Argon Mix	86		50 — 450	ipm (1.27 — 11.43 m/min)				

□ HyperFill Key Required

◆ HDT Key Required

△ Tandem Controller Required

* Range is limited by power source rating, module rating, or feeder configuration

			Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)	
	Type	Size							
GMAW	Aluminum (AlSi)	1.0 mm	GMAW CV	CV	Argon	148	Pinch	125 — 800 ipm	(3.18 — 20.32 m/min)
			GMAW Pulse	Pulse	Argon	149	UltimArc®	125 — 800 ipm	(3.18 — 20.32 m/min)
				CC Pulse	Argon	150		125 — 800 ipm	(3.18 — 20.32 m/min)
		GMAW Pulse on Pulse*	Pulse on Pulse*	Argon	98	Frequency	100 — 500 ipm	(2.54 — 12.7 m/min)	
		1.2 mm	GMAW CV	CV	Argon	71	Pinch	125 — 700 ipm	(3.18 — 17.78 m/min)
			GMAW Pulse	Pulse	Argon	72	UltimArc®	85 — 600 ipm	(2.16 — 15.24 m/min)
				CC Pulse	Argon	69		85 — 600 ipm	(2.16 — 15.24 m/min)
		GMAW Pulse on Pulse*	Pulse on Pulse*	Argon	99	Frequency	85 — 500 ipm	(2.16 — 12.7 m/min)	
		1.6 mm	GMAW CV	CV	Argon	73	Pinch	75 — 375 ipm	(1.91 — 9.53 m/min)
	GMAW Pulse		Pulse	Argon	74	UltimArc®	75 — 350 ipm	(1.91 — 8.89 m/min)	
			CC Pulse	Argon	79		75 — 350 ipm	(1.91 — 8.89 m/min)	
	GMAW Pulse on Pulse*	Pulse on Pulse*	Argon	100	Frequency	80 — 400 ipm	(2.03 — 10.16 m/min)		
	Aluminum (AlMg)	1.0 mm	GMAW CV	CV	Argon	151	Pinch	175 — 750 ipm	(4.45 — 19.05 m/min)
			GMAW Pulse	Pulse	Argon	152	UltimArc®	125 — 700 ipm	(3.18 — 17.78 m/min)
				CC Pulse	Argon	153		125 — 700 ipm	(3.18 — 17.78 m/min)
		GMAW Pulse on Pulse*	Pulse on Pulse*	Argon	101	Frequency	140 — 800 ipm	(3.56 — 20.32 m/min)	
		1.2 mm	GMAW CV	CV	Argon	75	Pinch	125 — 750 ipm	(3.18 — 19.05 m/min)
			GMAW Pulse	Pulse	Argon	76	UltimArc®	85 — 700 ipm	(2.16 — 17.78 m/min)
				CC Pulse	Argon	70		85 — 700 ipm	(2.16 — 17.78 m/min)
		GMAW Pulse on Pulse*	Pulse on Pulse*	Argon	102	Frequency	100 — 600 ipm	(2.54 — 15.24 m/min)	
		1.6 mm	GMAW CV	CV	Argon	77	Pinch	125 — 500 ipm	(3.18 — 12.7 m/min)
			GMAW Pulse	Pulse	Argon	78	UltimArc®	100 — 500 ipm	(2.54 — 12.7 m/min)
				CC Pulse	Argon	80		100 — 450 ipm	(2.54 — 11.43 m/min)
		GMAW Pulse on Pulse*	Pulse on Pulse*	Argon	103	Frequency	75 — 350 ipm	(1.91 — 8.89 m/min)	
SiBr	1.0mm	GMAW Pulse	Pulse	Argon	192	UltimArc®	80 — 1000 ipm	(2.03 — 25.4 m/min)	
	1.2mm	GMAW Pulse	Pulse	Argon	191	UltimArc®	50 — 600 ipm	(1.27 — 15.24 m/min)	
Cu	1.0mm	GMAW Pulse	Pulse	Argon Helium	198	UltimArc®	75 — 500 ipm	(1.91 — 12.7 m/min)	
	1.2mm	GMAW Pulse	Pulse	Argon Helium	196	UltimArc®	75 — 500 ipm	(1.91 — 12.7 m/min)	
NiCr	1.0mm	GMAW Pulse	Pulse	Ar/ Ar He	502	UltimArc®	75 — 800 ipm	(1.91 — 20.32 m/min)	
	1.2mm	GMAW Pulse	Pulse	Ar/ Ar He	504	UltimArc®	75 — 600 ipm	(1.91 — 15.24 m/min)	
FCAW	Flux Core	All	FCAW-S	Self Shield CV	NA	6	Pinch	10 — 45 V	
			FCAW-G	Gas Shield CV	NA	7	Pinch	10 — 45 V	
	Cored Wire	1.2 mm	FCAW-G	CV	CO ₂	90	Pinch	175 — 600 ipm	(4.45 — 15.24 m/min)
			Argon Mix	91	175 — 600 ipm	(4.45 — 15.24 m/min)			
		1.4 mm	FCAW-G	CV	CO ₂	187	Pinch	150 — 500 ipm	(3.81 — 12.7 m/min)
			Argon Mix	188	150 — 500 ipm	(3.81 — 12.7 m/min)			
		1.6 mm	FCAW-G	CV	CO ₂	189	Pinch	125 — 400 ipm	(3.18 — 10.16 m/min)
Argon Mix	190		125 — 400 ipm	(3.18 — 10.16 m/min)					
SMAW	NA	NA	DCEP SMAW	SMAW Soft	NA	1	Arc Force, Hot Start	15 — 900 A	
				SMAW Crisp	NA	2	Arc Force, Hot Start	15 — 900 A	
				SMAW Pipe	NA	4	Arc Force	50 — 250 A	
GTAW	NA	NA	DCEN GTAW	Touch Start TIG	Ar / He	3	Hot Start	5 — 900 A	
				Touch Start TIG Pulse	Ar / He	8	Frequency, Background, Hot Start	5 — 800 A	
				Auto TIG	AR / He	490		5 — 500 A	
CAG	NA	NA	CAG	Arc Gouge	Compressed Air	9		60 — 900 A	

□ HyperFill Key Required

◆ HDT Key Required

Δ Tandem Controller Required

* Range is limited by power source rating, module rating, or feeder configuration

GMAW - Tandem	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)	
	Steel	1.0 mm	GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	402	UltimArc®, Phase Angle	150 – 800 ipm	(3.81 – 20.32 m/min)
Sync Pulse Trail				Argon Mix	403	UltimArc®	150 – 800 ipm	(3.81 – 20.32 m/min)	
HotWire Pulse Trail				Argon Mix	461		80 – 800 ipm	(2.03 – 20.32 m/min)	
1.2 mm		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	404	UltimArc®, Phase Angle	100 – 700 ipm	(2.54 – 17.78 m/min)	
			Sync Pulse Trail	Argon Mix	405	UltimArc®	100 – 700 ipm	(2.54 – 17.78 m/min)	
			HotWire Pulse Trail	Argon Mix	462		75 – 800 ipm	(1.91 – 20.32 m/min)	
1.4 mm		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	406	UltimArc®, Phase Angle	100 – 600 ipm	(2.54 – 15.24 m/min)	
			Sync Pulse Trail	Argon Mix	407	UltimArc®	100 – 600 ipm	(2.54 – 15.24 m/min)	
			HotWire Pulse Trail	Argon Mix	463		50 – 800 ipm	(1.27 – 20.32 m/min)	
1.6 mm		GMAW Tandem (Δ)	Sync Pulse Lead	Argon Mix	408	UltimArc®, Phase Angle	100 – 500 ipm	(2.54 – 12.7 m/min)	
			Sync Pulse Trail	Argon Mix	409	UltimArc®	100 – 500 ipm	(2.54 – 12.7 m/min)	
			HotWire Pulse Trail	Argon Mix	464		50 – 500 ipm	(1.27 – 12.7 m/min)	

GMAW - HyperFill ¹	Type	Size	Procedure	Waveform	Gas Type	Mode #	Arc Control	Max. Range (*)		
	Steel	0.9mm	GMAW	HyperFill		Argon Mix	601		100 – 800 ipm	(2.54 – 20.32 m/min)
		1.0mm	GMAW	HyperFill		Argon Mix	602		100 – 700 ipm	(2.54 – 17.78 m/min)
		1.2mm	GMAW	HyperFill		Argon Mix	603		100 – 465 ipm	(2.54 – 11.81 m/min)
	Metal Core	1.2mm	GMAW	HyperFill		Argon Mix	608		100 - 515 ipm	(2.54 - 13.08 m/min)
	FCAW-G	1.2mm	GMAW	HyperFill		Argon Mix	618		100 - 430 ipm	(2.54 - 10.92 m/min)

¹HyperFill® & Process HDT™ Waveform Activation Capability with Power Wave® and PIPEFAB™ Systems

Your purchase of a Lincoln Power Wave or PIPEFAB Welding System comes with (i) a license to use Lincoln Electric standard Power Wave / PIPEFAB waveforms, and (ii) HyperFill & Process HDT waveform capability, which requires a separate license. Without the separate license, the HyperFill and Process HDT waveforms are not available for use on these machines, and only the standard Power Wave / PIPEFAB waveforms are usable.