



SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Tech-rod® 112 Product Size: 3/16" (4.8 mm)

Other means of identification

SDS number: 200000001176

Recommended use and restriction on use

Recommended use: SMAW (Shielded Metal Arc Welding)

Restrictions on use: Not known. Read this SDS before using this product.

Manufacturer/Importer/Supplier/Distributor Information

Company Name: The Lincoln Electric Company
Address: 22801 Saint Clair Avenue
Cleveland, Ohio 44117

USA

Telephone: +1 (216) 481-8100

Contact Person: Safety Data Sheet Questions: www.lincolnelectric.com/sds

Arc Welding Safety Information: www.lincolnelectric.com/safety

Company Name: Lincoln Electric Mexicana S.A. de C.V. Address: Calz. Azcapotzalco La Villa No. 869

Delegacion Azcapotzalco 02300 Mexico, D.F.

Mexico

Telephone: +1 52 55 5063 0030

Contact Person: Safety Data Sheet Questions: www.lincolnelectric.com/sds

Arc Welding Safety Information: www.lincolnelectric.com/safety

Company Name: The Lincoln Electric Company of Canada LP

Address: 179 Wicksteed Avenue

Toronto, Ontario M4G 2B9

Canada

Telephone: +1 (416) 421-2600

Contact Person: Safety Data Sheet Questions: www.lincolnelectric.com/sds

Arc Welding Safety Information: www.lincolnelectric.com/safety

Emergency telephone number:

USA/Canada/Mexico +1 (888) 609-1762 Americas/Europe +1 (216) 383-8962 Asia Pacific +1 (216) 383-8966 Middle East/Africa +1 (216) 383-8969

3E Company Access Code: 333988

2. HAZARDS IDENTIFICATION

Classified according to the criteria of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), The United States Occupational Safety and Health Administration's Hazard Communication Standard (29 CFR 1910.1200), Canada's Hazardous Product Regulations and Mexico's Harmonized System for the Identification and Communication of Hazards and Risks from Hazardous Chemicals in the Workplace.

Hazard Classification Not classified as hazardous according to applicable GHS hazard classification

criteria.



Label Elements

Hazard Symbol: No symbol

Signal Word: No signal word.

Hazard Statement: Not applicable

Precautionary Statements:

Not applicable

Other hazards which do not result in GHS classification:

Electrical Shock can kill. If welding must be performed in damp locations or with wet clothing, on metal structures or when in cramped positions such as sitting, kneeling or lying, or if there is a high risk of unavoidable or

accidental contact with work piece, use the following equipment:

Semiautomatic DC Welder, DC Manual (Stick) Welder, or AC Welder with

Reduced Voltage Control.

Arc rays can injure eyes and burn skin. Welding arc and sparks can ignite combustibles and flammable materials. Overexposure to welding fumes and gases can be hazardous. Read and understand the manufacturer's instructions, Safety Data Sheets and the precautionary labels before using this product. Refer to Section 8.

Substance(s) formed under the conditions of use:

The welding fume produced from this welding electrode may contain the following constituent(s) and/or their complex metallic oxides as well as solid particles or other constituents from the consumables, base metal, or base metal coating not listed below.

Chemical Identity	CAS-No.
Carbon dioxide	124-38-9
Carbon monoxide	630-08-0
Nitrogen dioxide	10102-44-0
Ozone	10028-15-6
Manganese	7439-96-5
Chromium (VI)	18540-29-9
Nickel	7440-02-0
Chromium oxide	1308-38-9
Fluorides (as F)	16984-48-8

3. COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Ingredients Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Nickel	7440-02-0	20 - <50%
Chromium and chromium alloys or compounds (as Cr)	7440-47-3	10 - <20%
Molybdenum	7439-98-7	5 - <10%
Titanium dioxide (synthetic)	13463-67-7	5 - <10%
Limestone	1317-65-3	1 - <5%
Niobium	7440-03-1	1 - <5%
Cryolite	15096-52-3	1 - <5%





Calcium fluoride	7789-75-5	1 - <5%
Titanium dioxide (naturally occurring)	13463-67-7	1 - <5%
Sodium silicate	1344-09-8	1 - <5%
Iron	7439-89-6	1 - <5%
Manganese	7439-96-5	0.1 - <1%
Potassium hydroxide	1310-58-3	0.1 - <1%
Titanium	7440-32-6	0.1 - <1%
Vanadium alloys (as V)	7440-62-2	0.1 - <1%
Tin	7440-31-5	0.1 - <1%
Tungsten	7440-33-7	0.1 - <1%
Zinc	7440-66-6	0.1 - <1%
Potassium oxide	12136-45-7	0.1 - <1%
Bentonite	1302-78-9	0.1 - <1%
Copper and/or copper alloys and compounds (as Cu)	7440-50-8	0.1 - <1%
Aluminum and/or aluminum alloys (as Al)	7429-90-5	0.1 - <1%
Silicon	7440-21-3	0.1 - <1%
Silicon dioxide (amorphous)	7631-86-9	0.1 - <1%
Magnesite	546-93-0	0.1 - <1%
Sodium alginate	9005-38-3	0.1 - <1%
Potassium carbonate	584-08-7	0.1 - <1%
Quartz	14808-60-7	0.1 - <1%
Cobalt and compounds (as Co)	7440-48-4	0.1 - <1%
Iron oxide	1309-37-1	0.1 - <1%
		•

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments:

The term "Hazardous Ingredients" should be interpreted as a term defined in Hazard Communication standards and does not necessarily imply the existence of a welding or allied process hazard. The product may contain additional non-hazardous ingredients or may form additional compounds under the condition of use. Refer to Sections 2 and 8 for more information.

4. FIRST AID MEASURES

Ingestion: Avoid hand, clothing, food, and drink contact with fluxes, metal fume or

powder which can cause ingestion of particulate during hand to mouth activities such as drinking, eating, smoking, etc. If ingested, do not induce vomiting. Contact a poison control center. Unless the poison control center advises otherwise, wash out mouth thoroughly with water. If symptoms

develop, seek medical attention at once.

Inhalation: Move to fresh air if breathing is difficult. If breathing has stopped, perform

artificial respiration and obtain medical assistance at once.

Skin Contact: Remove contaminated clothing and wash the skin thoroughly with soap and

water. For reddened or blistered skin, or thermal burns, obtain medical

assistance at once.

Eye contact: Dust or fume from this product should be flushed from the eyes with

copious amounts of clean, tepid water until transported to an emergency medical facility. Do not allow victim to rub or keep eyes tightly closed.

Obtain medical assistance at once.





Arc rays can injure eyes. If exposed to arc rays, move victim to dark room, remove contact lenses as necessary for treatment, cover eyes with a padded dressing and rest. Obtain medical assistance if symptoms persist.

Most important symptoms/effects, acute and delayed

Symptoms:

Short-term (acute) overexposure to fumes and gases from welding and allied processes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long-term (chronic) overexposure to fumes and gases from welding and allied processes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects. Refer to Section 11 for more information.

Section 11 for more information

Hazards: The hazards associated with welding and its allied processes such as

soldering and brazing are complex and may include physical and health hazards such as but not limited to electric shock, physical strains, radiation burns (eye flash), thermal burns due to hot metal or spatter and potential health effects of overexposure to fumes, gases or dusts potentially generated during the use of this product. Refer to Section 11 for more

information.

Indication of immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

General Fire Hazards: As shipped, this product is nonflammable. However, welding arc and

sparks as well as open flames and hot surfaces associated with brazing and soldering can ignite combustible and flammable materials. Read and understand American National Standard Z49.1, "Safety in Welding, Cutting and Allied Processes" and National Fire Protection Association NFPA 51B, "Standard for Fire Prevention during Welding, Cutting and Other Hot Work"

before using this product.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: As shipped, the product will not burn. In case of fire in the surroundings:

use appropriate extinguishing agent.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Welding arc and sparks can ignite combustibles and flammable products.

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures:

Use standard firefighting procedures and consider the hazards of other involved materials.

Special protective equipment

for fire-fighters:

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

If airborne dust and/or fume is present, use adequate engineering controls and, if needed, personal protection to prevent overexposure. Refer to





emergency procedures: recommendations in Section 8.

Methods and material for containment and cleaning up: Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk. Clean up spills immediately, observing precautions in the personal protective equipment in Section 8. Avoid generating dust. Prevent product from entering any drains, sewers or water sources. Refer to

Section 13 for proper disposal.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer. Environmental

manager must be informed of all major spillages.

7. HANDLING AND STORAGE

Precautions for safe handling: Prevent formation of dust. Provide appropriate exhaust ventilation at

places where dust is formed.

Read and understand the manufacturer's instruction and the precautionary

label on the product. Refer to Lincoln Safety Publications at

www.lincolnelectric.com/safety. See American National Standard Z49.1,

"Safety In Welding, Cutting and Allied Processes" published by the American Welding Society, http://pubs.aws.org and OSHA Publication 2206

(29CFR1910), U.S. Government Printing Office, www.gpo.gov.

Conditions for safe storage, including any incompatibilities: Store in closed original container in a dry place. Store in accordance with local/regional/national regulations. Store away from incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits: US

Chemical Identity	Туре	Exposure Limit Values	Source
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Nickel - as Ni	REL	0.015 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Nickel	IDLH	10 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Nickel - as Ni	PEL	1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Chromium and chromium alloys or compounds (as Cr) - as Cr	PEL	1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	0.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Chromium and chromium alloys or compounds (as Cr) - Inhalable fraction as Cr(0)	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
Chromium and chromium alloys or compounds (as Cr)	IDLH	250 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Molybdenum - Total dust as Mo	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Molybdenum - Inhalable fraction as Mo	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Molybdenum - Respirable fraction as Mo	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Molybdenum	IDLH	5,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Molybdenum - Respirable	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (01



particles.			2021)
Molybdenum - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (01 2021)
Molybdenum - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
Molybdenum - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000 (09 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
Titanium dioxide (synthetic)	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	IDLH	5,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Titanium dioxide (synthetic) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide (synthetic) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000 (03 2016)
Titanium dioxide (synthetic) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide (synthetic) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide (synthetic) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000 (03 2016)
Limestone - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Limestone - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Limestone - Respirable.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Limestone - Total	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Limestone - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (01 2021)
Limestone - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (01 2021)
Limestone - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000 (09 2016)
Limestone - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000 (09 2016)
Limestone - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000 (09 2016)
Limestone - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000 (09 2016)
Cryolite - as F	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Cryolite - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Cryolite - as F	REL	2.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	2.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cryolite - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000 (02 2006)
Cryolite	IDLH	250 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
	IDLH	250 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Calcium fluoride - as F	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values (12



			2010)
Calcium fluoride	IDLH	250 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
	IDLH	250 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Calcium fluoride - as F	PEL	2.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium fluoride - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
Titanium dioxide (naturally occurring)	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	IDLH	5,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Titanium dioxide (naturally occurring) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide (naturally occurring) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide (naturally occurring) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide (naturally occurring) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide (naturally occurring) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Manganese - Fume as Mn	Ceiling	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL	3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Manganese - Inhalable fraction as Mn	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Manganese - Respirable fraction as Mn	TWA	0.02 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Manganese	IDLH	500 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Potassium hydroxide	Ceiling	2 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
The second	Ceil_Time	2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Tin - as Sn	PEL	2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Tin	IDLH	100 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Tin - Inhalable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (01 2019)
Tungsten - as W	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Tungsten - Respirable fraction as W	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	TWA	0.2 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
	REL	0.1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Copper and/or copper alloys and compounds (as Cu) -	REL	1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)



Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	Dust and mist as Cu			
and compounds (as Cu) - Furner - as Cu Copper and/or copper alloys and compounds (as Cu) - 2006 Copper and/or copper alloys and compounds (as Cu) - 2006 Dust and mist - as Cu Copper and/or copper alloys and compounds (as Cu) - 2006 Dust and mist - as Cu Copper and/or copper alloys and compounds (as Cu) - 2006 Silicon - Respirable fraction. PEL 15 mg/m3 US, NCSH, Immediately Dangerous to 2006 US, NCSH, Immediately Dangerous to 2006 US, NCSH, Immediately Dangerous to 2006 US, NCSH, Trenshold Limit Values (10 2017) US, NCSH, Trens		PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air
Fume - as Cu	and compounds (as Cu) -		3	Contaminants (29 CFR 1910.1000) (02
and compounds (as Cu) - Dust and mist as Cu Copper and/or copper alloys DLH 100 mg/m3 US. NIOSH. Immediately Dangerous US. ACGIH Threshold Limit Values (12 2010) US. AUMINIUM and/or aluminum alloys (as Al) - Volidid pume of prophoric powder as Al Aluminum and/or aluminum alloys (as Al) - Welding time of prophoric powder as Al Aluminum and/or aluminum alloys (as Al) - Respirable. Smg/m3 US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-3 (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-3 (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-3 (20 CFR 1910.1000) (03 2016) US. OSHA Tab				
and compounds (as Cu) - Dust and mist as Cu Copper and/or copper alloys DLH 100 mg/m3 US. NIOSH. Immediately Dangerous US. ACGIH Threshold Limit Values (12 2010) US. AUMINIUM and/or aluminum alloys (as Al) - Volidid pume of prophoric powder as Al Aluminum and/or aluminum alloys (as Al) - Welding time of prophoric powder as Al Aluminum and/or aluminum alloys (as Al) - Respirable. Smg/m3 US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. NIOSH Pooket Guide to Chemical Hazards, as amended (2005) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-3 (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-3 (20 CFR 1910.1000) (03 2016) US. OSHA Table Z-3 (20 CFR 1910.1000) (03 2016) US. OSHA Tab	Copper and/or copper alloys	PEL	1 mg/m3	US. OSHA Table Z-1 Limits for Air
Dust and mist as Cu Cooper and/or opper alloys DLH 100 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Values (10 2018) Values (10 2017) Values (10 201			3	
and compounds (as Cu) Aluminum and/or aluminum alloys (as A) - Respirable fraction. Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Vedeting furne or prophorbro powder - as Al Aluminum and/or aluminum alloys (as A) - Welding furne or prophorbro powder - as Al Aluminum and/or aluminum alloys (as A) - Welding furne or prophorbro powder - as Al Aluminum and/or aluminum alloys (as A) - Total dust. BEL Aluminum and/or aluminum alloys (as A) - Total Aluminum and/or aluminum alloys (as A) - Respirable fraction - as Al BEL 5 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Silicon - Total dust. PEL 5 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Respirable fraction. PEL 5 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Respirable particles. TWA 3 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Respirable particles. TWA 3 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Total dust. TWA 3 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Total dust. TWA 3 mg/m3 JUS, OSHA Table 2-3 (29 CFR 1910.1000) (09 2016) Silicon - Total dust. TWA 3 mg/m3 JUS, OSHA Table 2-3 (29 CFR 1910.1000) (19 2016) Silicon - Respirable fraction. TWA 3 mg/m3 JUS, OSHA Table 2-3 (29 CFR 1910.1000) (19 2016)				
and compounds (as Cu) Aluminum and/or aluminum alloys (as A) - Respirable fraction. Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Total dust. as Al Aluminum and/or aluminum alloys (as A) - Vedeting furne or prophorbro powder - as Al Aluminum and/or aluminum alloys (as A) - Welding furne or prophorbro powder - as Al Aluminum and/or aluminum alloys (as A) - Welding furne or prophorbro powder - as Al Aluminum and/or aluminum alloys (as A) - Total dust. BEL Aluminum and/or aluminum alloys (as A) - Total Aluminum and/or aluminum alloys (as A) - Respirable fraction - as Al BEL 5 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Silicon - Total dust. PEL 5 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Respirable fraction. PEL 5 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Respirable particles. TWA 3 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Respirable particles. TWA 3 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Total dust. TWA 3 mg/m3 JUS, OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Silicon - Total dust. TWA 3 mg/m3 JUS, OSHA Table 2-3 (29 CFR 1910.1000) (09 2016) Silicon - Total dust. TWA 3 mg/m3 JUS, OSHA Table 2-3 (29 CFR 1910.1000) (19 2016) Silicon - Respirable fraction. TWA 3 mg/m3 JUS, OSHA Table 2-3 (29 CFR 1910.1000) (19 2016)	Copper and/or copper allovs	IDLH	100 mg/m3	US, NIOSH, Immediately Dangerous to
Aluminum and/or aluminum alloys (as A) - Respirable PEL 15 mg/m3 US. OSHA Table 2.1 Limits for Air Contaminants (29 CFR 1910.1000) (02 as A) - Total dust as Al Aluminum and/or aluminum alloys (as A) - Total dust as Al Aluminum and/or aluminum alloys (as A) - Welding furne or pyrophorio powder - as Al Aluminum and/or aluminum alloys (as A) - Welding furne or pyrophorio powder - as Al Aluminum and/or aluminum alloys (as A) - Respirable. REL 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pock			gg	
Aluminum and/or aluminum and		TWA	1 mg/m3	US. ACGIH Threshold Limit Values (12
			·9	
Aluminum and/or aluminum alloys (as A) - Total dust				20.0)
Aluminum and/or aluminum REL 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) Aluminum and/or aluminum REL 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) Aluminum and/or aluminum REL 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) Aluminum and/or aluminum REL 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) Aluminum and/or aluminum REL 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) Aluminum and/or aluminum REL 10 mg/m3 US. OSHA Table 2-1 Limits for Air Contaminants (29 GFR 1910.1000) (03 2016) Contaminants (29 GFR 1910.1000) (03 2016) Contaminants (29 GFR 1910.1000) (07 2006) Contaminants (29 GFR 1910.1000) (08 2006) Contaminants (29 GFR 1910.1000) (09 2006) Contaminants (2		PEI	15 mg/m3	LIS OSHA Table 7-1 Limits for Air
SA		'	13 1119/1113	
Aluminum and/or aluminum and/or aluminum alloys (as A) - Welding furme or pyrophoric powder as Al Aluminum and/or aluminu				
Aluminum and/or aluminum alloys (as Al.) - Welding furne or pyrophoric powder as Al		DEI	5 ma/m2	
or pyrophoric powder as Al Aluminum and/or		NLL	3 mg/m3	
Aluminum and/or aluminum alloys (as Al) - Respirable REL 5 mg/m3 US. NIOSH- Pocket Guide to Chemical Aluminum and/or a				Hazarus, as amenueu (2005)
Aluminum and/or aluminum aldoys (as Al) - Total PEL S mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (10 Contaminants (20 CFR 1910.1000) (10 Contaminants (29 CFR 1910.1000) (10 Contaminants (20 CFR 1910.1000	Alversiones and for alversiones	DEL	F/2	LIC NICCLE Desirat Cuida to Chamical
Aluminum and/or aluminum Alum		KEL	5 mg/m3	
Aluminum and/or aluminum PEL 5 mg/m3 US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 216)				
Aluminum and/or aluminum aloys (as Al.) - Respirable fraction as Al		REL	10 mg/m3	
Alloys (as Al) - Respirable Fraction. as Al				
Fraction - as Al	Aluminum and/or aluminum	PEL	5 mg/m3	
Silicon - Total dust.				Contaminants (29 CFR 1910.1000) (03
Silicon - Respirable fraction. PEL S mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (fraction as Al			
Silicon - Respirable fraction. PEL S mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	Silicon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
Silicon - Respirable fraction. PEL S mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2016)			3	
Contaminants (29 CFR 1910.1000) (02 2006)				
Contaminants (29 CFR 1910.1000) (02 2006)	Silicon - Respirable fraction.	PFI	5 mg/m3	
Silicon - Respirable.	Cincon recopilable naction.	'	o mg/mo	
Silicon - Respirable. REL 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)				
Hazards, as amended (2005) Silicon - Total REL	Silicon Posnirable	DEI	5 mg/m ²	,
Silicon - Total REL 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) Silicon - Respirable particles. TWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Immediately Dangerous to Life or Health (IDLH) Values (10 2017) US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000)	Silicon - Respirable.	KEL	5 mg/ms	
Silicon - Respirable particles.	Ciliaan Tatal	DEI	10 = a/m2	
Silicon - Respirable particles. TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) US. ACGIH Threshold Limit Values (01 2021) US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) (09	Silicon - Total	KEL	10 mg/m3	
Silicon - Inhalable particles.				
Silicon - Inhalable particles. TWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021)	Silicon - Respirable particles.	IWA	3 mg/m3	
Silicon - Respirable fraction.				
Silicon - Respirable fraction. TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. OSHA Table Z-3 (29 CFR 1910.1000) (20	Silicon - Inhalable particles.	TWA	10 mg/m3	
Silicon - Total dust.				
Silicon - Total dust. TWA 50 millions of particles per cubic foot of air TWA 15 millions of particles per cubic foot of air Silicon - Respirable fraction. TWA 15 millions of particles per cubic foot of air Silicon dioxide (amorphous) REL 6 mg/m3 IDLH 3,000 mg/m3 Silicon dioxide (amorphous) - Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA TWA 15 millions of particles per cubic foot of air	Silicon - Respirable fraction.	TWA	5 mg/m3	
particles per cubic foot of air TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) Silicon - Respirable fraction. TWA 15 millions of particles per cubic foot of air Silicon dioxide (amorphous) TWA 20 millions of particles per cubic foot of air TWA 20 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - ITWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (10 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (10 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (10 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (10 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (10 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (10 2016)				
TWA	Silicon - Total dust.	TWA		US. OSHA Table Z-3 (29 CFR 1910.1000)
TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) Silicon - Respirable fraction. TWA 15 millions of particles per cubic foot of air Silicon dioxide (amorphous) TWA 20 millions of particles per cubic foot of air TWA 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) IDLH 3,000 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - TWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 50 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA 15 millions of particles per cubic foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000)			particles per cubic	(09 2016)
Silicon - Respirable fraction. Silicon dioxide (amorphous) TWA TWA TWA TWA TWA TWA TWA TW			foot of air	
Silicon - Respirable fraction. Silicon dioxide (amorphous) TWA TWA TWA TWA TWA TWA TWA TW		TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000)
Silicon - Respirable fraction. Silicon dioxide (amorphous) TWA 20 millions of particles per cubic foot of air Silicon dioxide (amorphous) TWA 20 millions of particles per cubic foot of air TWA 20 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH: Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - ITWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 5 millions of particles per cubic foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)			3	
Silicon dioxide (amorphous) TWA 20 millions of particles per cubic (2000) TWA 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) IDLH 3,000 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) US. ACGIH Threshold Limit Values (01 2021) TWA 50 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA TWA 50 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)	Silicon - Respirable fraction	TWA	15 millions of	
Silicon dioxide (amorphous) TWA 20 millions of particles per cubic foot of air TWA 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - INAlalable particles. Silicon dioxide (amorphous) - TWA Somillions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA Somillions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA Somillions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA Somillions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA Somillions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)				(09 2016)
Silicon dioxide (amorphous) TWA 20 millions of particles per cubic foot of air TWA 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) IDLH 3,000 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA Silic				(
particles per cubic foot of air TWA 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - ITWA Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous)	Silicon diovide (amorphous)	TWΔ		US OSHA Table 7-3 (20 CEP 1010 1000)
TWA TWA TWA TWA TWA TWA TWA TWA	Smooth dioxide (difforprious)	1 **/ 1		
TWA O.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA TWA TWA TWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (99 2016) TWA TWA TWA TWA TWA TWA US. OSHA Table Z-3 (29 CFR 1910.1000)			·	(2000)
REL 6 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005) IDLH 3,000 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - TWA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 50 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA 15 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA 15 millions of particles per cubic foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000)		TIMA		LIC OCUA Toble 7.2 (20 CER 1010 1000)
REL Bilicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - TWA Si		IVVA	0.8 mg/m3	
Hazards, as amended (2005) IDLH 3,000 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - ITWA Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - TW				
Silicon dioxide (amorphous) - IVA 10 mg/m3 US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)		KEL	6 mg/m3	
Life or Health (IDLH) Values (10 2017) Silicon dioxide (amorphous) - Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - Respirable fraction. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) -				` ′
Silicon dioxide (amorphous) - INA 10 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA 3 mg/m3 US. ACGIH Threshold Limit Values (01 2021) Silicon dioxide (amorphous) - TWA 50 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA 15 millions of particles per cubic foot of air Silicon dioxide (amorphous) - TWA 15 millions of particles per cubic foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000)		IDLH	3,000 mg/m3	
Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) - TWA TWA Silicon dioxide (amorphous) - TWA Sil				Life or Health (IDLH) Values (10 2017)
Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) - TWA TWA Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) - TWA Silicon dioxide		TWA	10 mg/m3	US. ACGIH Threshold Limit Values (01
Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) -	Silicon dioxide (amorphous) -		_	
Respirable particles. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) - TWA Silicon dioxide (amorphous) - Respirable fraction. TWA Silicon dioxide (amorphous) - TWA Silicon dioxide		<u> </u>		2021)
Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) - Respirable fraction. TWA Somillions of particles per cubic foot of air TWA Somillions of particles per cubic foot of air 15 millions of particles per cubic foot of air TWA Somillions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles.		3 ma/m3	
Total dust. particles per cubic foot of air Silicon dioxide (amorphous) - Respirable fraction. TWA particles per cubic foot of air 15 millions of particles per cubic foot of air TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) TWA US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles. Silicon dioxide (amorphous) -		3 mg/m3	US. ACGIH Threshold Limit Values (01
Silicon dioxide (amorphous) - Respirable fraction. TWA 15 millions of particles per cubic foot of air TWA 15 millions of particles per cubic foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles.	TWA		US. ACGIH Threshold Limit Values (01 2021)
Silicon dioxide (amorphous) - Respirable fraction. TWA 15 millions of particles per cubic foot of air TWA 15 millions of particles per cubic foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) -	TWA	50 millions of	US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000)
Respirable fraction. particles per cubic foot of air TWA particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) -	TWA	50 millions of particles per cubic	US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000)
foot of air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000)	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) -	TWA	50 millions of particles per cubic foot of air 15 millions of	US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000)
	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) -	TWA	50 millions of particles per cubic foot of air 15 millions of particles per cubic	US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000)
	Inhalable particles. Silicon dioxide (amorphous) - Respirable particles. Silicon dioxide (amorphous) - Total dust. Silicon dioxide (amorphous) -	TWA TWA	50 millions of particles per cubic foot of air 15 millions of particles per cubic foot of air	US. ACGIH Threshold Limit Values (01 2021) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)





Silicon dioxide (amorphous) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
Magnesite - Total	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Magnesite - Respirable.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (01 2021)
Magnesite - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (01 2021)
Magnesite - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
Magnesite - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (09 2016)
Quartz - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Quartz - Respirable dust.	REL	0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Quartz - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (03 2016)
Quartz - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Quartz	IDLH	50 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Quartz - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (02 2020)
Cobalt and compounds (as Co) - Dust and fume as Co	REL	0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cobalt and compounds (as Co)	IDLH	20 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Cobalt and compounds (as Co) - Inhalable fraction as Co	TWA	0.02 mg/m3	US. ACGIH Threshold Limit Values (01 2021)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Dust and fume as Fe	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Iron oxide	IDLH	2,500 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)

Occupational Exposure Limits: Canada

Chemical Identity	Туре	Exposure Limit Values	Source
-------------------	------	-----------------------	--------



Nickel	TWA	1.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Nickel - as Ni	TWA	0.05 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Nickel - Inhalable fraction as Ni	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	8 HR ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Nickel - Inhalable dust.	TWA	1.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Chromium and chromium alloys or compounds (as Cr) - as Cr	TWA	0.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	0.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Chromium and chromium alloys or compounds (as Cr)	TWA	0.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Chromium and chromium alloys or compounds (as Cr) - Inhalable fraction as Cr(0)	TWA	0.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
Chromium and chromium alloys or compounds (as Cr) - Total	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Molybdenum - Inhalable fraction as Mo	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Molybdenum - Respirable fraction as Mo	8 HR ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Molybdenum - Inhalable fraction as Mo	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Molybdenum - Respirable fraction as Mo	15 MIN ACL	6 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006,



			The Workplace Safety And Health Act), as amended (03 2014)
Molybdenum - Inhalable fraction as Mo	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
Molybdenum - Respirable fraction as Mo	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Molybdenum - Total particulate.	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (01 2019)
Molybdenum - Respirable particles.	TWA	3 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (01 2019)
Molybdenum - Respirable as Mo	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Molybdenum - Inhalable - as Mo	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Molybdenum - Inhalable particles.	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Molybdenum - Respirable particles.	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Molybdenum - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Molybdenum - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Molybdenum - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Molybdenum - Respirable dust as Mo	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Molybdenum - Inhalable dust. - as Mo	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Titanium dioxide (synthetic)	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Titanium dioxide (synthetic) - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide (synthetic) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide (synthetic)	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)



	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Titanium dioxide (synthetic) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Limestone	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Limestone - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Limestone - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Limestone	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Limestone - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Limestone - Inhalable particles.	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Limestone - Respirable particles.	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Limestone - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Limestone - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Limestone - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Limestone - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Cryolite - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
-	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07



			2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Cryolite - Respirable fraction.	TWA	1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Cryolite - as F	TWA	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cryolite - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cryolite - as F	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Cryolite - Dust as Al	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Cryolite - as F	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cryolite - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Calcium fluoride - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	TWA	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Titanium dioxide (naturally occurring)	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Titanium dioxide (naturally	TWA	10 mg/m3	Canada. British Columbia OELs.



	ı		
occurring) - Total dust.			(Occupational Exposure Limits for Chemical Biological Substances,
			Occupational Health and Safety
			Regulation 296/97, as amended) (07 2007)
Titanium dioxide (naturally	TWA	3 mg/m3	Canada. British Columbia OELs.
occurring) - Respirable		-	(Occupational Exposure Limits for
fraction.			Chemical Biological Substances,
			Occupational Health and Safety Regulation 296/97, as amended) (07
			2007)
Titanium dioxide (naturally	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006,
occurring)			The Workplace Safety And Health Act), as amended (03 2011)
	TWA	10 mg/m3	Canada. Ontario OELs. (Control of
			Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs
			(Occupational Health and Safety
			Regulations, 1996, Table 21), as
	15 MIN	20	amended (05 2009) Canada, Saskatchewan OELs
	ACL	20 mg/m3	(Occupational Health and Safety
	7.02		Regulations, 1996, Table 21), as
			amended (05 2009)
Titanium dioxide (naturally	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor
occurring) - Total dust.			- Regulation respecting occupational health and safety), as amended (09 2017)
Manganese - as Mn	TWA	0.2 mg/m3	Canada. Alberta OELs (Occupational
9		S	Health & Safety Code, Schedule 1, Table
	0.115.401		2), as amended (07 2009)
	8 HR ACL	0.2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety
			Regulations, 1996, Table 21), as
			amended (05 2009)
	15 MIN	0.6 mg/m3	Canada. Saskatchewan OELs
	ACL		(Occupational Health and Safety Regulations, 1996, Table 21), as
			amended (05 2009)
Manganese - Respirable	TWA	0.02 mg/m3	Canada. Manitoba OELs (Reg. 217/2006,
fraction as Mn			The Workplace Safety And Health Act), as amended (03 2014)
Manganese - Inhalable	TWA	0.1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006,
fraction as Mn			The Workplace Safety And Health Act), as amended (03 2014)
Manganese - as Mn	TWA	0.2 mg/m3	Canada. Ontario OELs. (Control of
manganess as min		0. _ g,	Exposure to Biological or Chemical
			Agents), as amended (06 2015)
Manganese - Fume, total	TWA	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor
dust as Mn			- Regulation respecting occupational health and safety), as amended (09 2017)
Manganese - Respirable as	TWA	0.02 mg/m3	Canada. British Columbia OELs.
Mn		S	(Occupational Exposure Limits for
			Chemical Biological Substances,
			Occupational Health and Safety Regulation 296/97, as amended) (07
			2018)
Manganese - Total - as Mn	TWA	0.2 mg/m3	Canada. British Columbia OELs.
			(Occupational Exposure Limits for
			Chemical Biological Substances, Occupational Health and Safety
			Regulation 296/97, as amended) (07
			2018)
Potassium hydroxide	CEILING	2 mg/m3	Canada. Alberta OELs (Occupational
			Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	CEILING	2 mg/m3	Canada. British Columbia OELs.
		3 ,c	(Occupational Exposure Limits for
			Chemical Biological Substances,
			Occupational Health and Safety
			Regulation 296/97, as amended) (07



	T T		
	CEILING	2 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	CEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (07 2010)
	Ceiling	2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	CEILING	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Tin - as Sn	TWA	2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Tin	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tin - as Sn	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	4 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Tin	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Tin - Inhalable fraction.	TWA	2 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2019)
Tungsten - as W	STEL	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Tungsten	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tungsten - as W	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor



			- Regulation respecting occupational
	STEL	10 mg/m3	health and safety), as amended (09 2017) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational
Tungsten - Respirable fraction as W	TWA	3 mg/m3	health and safety), as amended (09 2017) Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as
Copper and/or copper alloys and compounds (as Cu) - Fume.	TWA	0.2 mg/m3	amended (03 2017) Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	TWA	1 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	TWA	0.2 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
Copper and/or copper alloys and compounds (as Cu) - Dust and fume as Cu	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	8 HR ACL	1 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	15 MIN ACL	0.6 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	15 MIN ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	8 HR ACL	0.2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	TWA	1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	TWA	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder as Al	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Aluminum and/or aluminum alloys (as Al) - Dust.	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Aluminum and/or aluminum alloys (as Al) - Respirable fraction.	TWA	1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical



			Agents), as amended (11 2010)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder as Al	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Aluminum and/or aluminum alloys (as Al) - Dust as Al	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder as Al	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Aluminum and/or aluminum alloys (as Al) - Dust as Al	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Aluminum and/or aluminum alloys (as Al)	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum and/or aluminum alloys (as Al) - as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum and/or aluminum alloys (as Al) - Welding fume as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum and/or aluminum alloys (as Al) - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon - Total dust.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (07 2010)
Silicon	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Silicon - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Silicon - Respirable particles.	TWA	3 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (01 2019)
Silicon - Total particulate.	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (01 2019)
Silicon - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon - Inhalable particles.	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Silicon - Respirable particles.	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Silicon - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical



			Agents), as amended (01 2020)
Silicon - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical
			Agents), as amended (01 2020)
Silicon - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical
			Agents), as amended (01 2020)
Silicon - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical
			Agents), as amended (01 2020)
Silicon dioxide (amorphous)	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical
			Agents), as amended (07 2010)
Silicon dioxide (amorphous) - Total particulate.	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table
			2), as amended (01 2019)
Silicon dioxide (amorphous) - Respirable particles.	TWA	3 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table
	=1444		2), as amended (01 2019)
Silicon dioxide (amorphous) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon dioxide (amorphous) -	TWA	10 mg/m3	Canada. British Columbia OELs.
Total dust.		Ü	(Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06
O'l' l' '-l - (l)	TIALA	0/ 0	2020)
Silicon dioxide (amorphous) - Respirable particles.	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Silicon dioxide (amorphous) -	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006,
Inhalable particles.		To mg/mo	The Workplace Safety And Health Act), as amended (01 2021)
Silicon dioxide (amorphous) -	TWA	3 mg/m3	Canada. Ontario OELs. (Control of
Respirable fraction.		, and the second	Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon dioxide (amorphous) -	TWA	10 mg/m3	Canada. Ontario OELs. (Control of
Inhalable particles.			Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon dioxide (amorphous) -	TWA	10 mg/m3	Canada. Ontario OELs. (Control of
Inhalable fraction.		-	Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon dioxide (amorphous) -	TWA	3 mg/m3	Canada. Ontario OELs. (Control of
Respirable particles.			Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon dioxide (amorphous) -	15 MIN	20 mg/m3	Canada. Saskatchewan OELs
Inhalable fraction.	ACL		(Occupational Health and Safety
			Regulations, 1996, Table 21), as amended (06 2016)
Silicon dioxide (amorphous) -	15 MIN	6 mg/m3	Canada. Saskatchewan OELs
Respirable fraction.	ACL	5g,c	(Occupational Health and Safety Regulations, 1996, Table 21), as
			amended (06 2016)
	8 HR ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as
			amended (06 2016)
Silicon dioxide (amorphous) - Inhalable fraction.	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as
			amended (06 2016)
Silicon dioxide (amorphous) -	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor
Total dust.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	10 mg/ms	- Regulation respecting occupational health and safety), as amended (03 2020)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of
-		Ç i	Exposure to Biological or Chemical Agents), as amended (07 2010)



Magnesite	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety
			Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Magnesite - Respirable particles.	TWA	3 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (01 2019)
Magnesite - Total particulate.	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (01 2019)
Magnesite - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Magnesite - Respirable particles.	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Magnesite - Inhalable particles.	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Magnesite - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Magnesite - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Magnesite - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Magnesite - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Quartz - Respirable particles.	TWA	0.025 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Quartz - Respirable fraction.	8 HR ACL	0.05 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Quartz - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Quartz - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
	TWA	0.025 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Cobalt and compounds (as Co) - as Co	TWA	0.02 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)



	TWA	0.02 mg/m3	Canada. Ontario OELs. (Control of
		•	Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	0.02 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	0.06 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	0.02 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cobalt and compounds (as Co) - Inhalable fraction as Co	TWA	0.02 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Iron oxide - Respirable.	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Iron oxide	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Iron oxide - Dust and fume as Fe	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)



TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor
		 Regulation respecting occupational
		health and safety), as amended (09 2017)

Chemical Identity	Туре	Exposure Limit Values	Source
Nickel - Inhalable fraction as Ni	VLE-PPT	1.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Chromium and chromium alloys or compounds (as Cr)	VLE-PPT	0.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
	VLE-PPT	0.05 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
	VLE-PPT	0.01 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Molybdenum - Respirable fraction as Mo	VLE-PPT	0.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Titanium dioxide (synthetic)	VLE-PPT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Limestone - Inhalable fraction.	VLE-PPT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Limestone - Respirable fraction.	VLE-PPT	3 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Cryolite - Respirable fraction.	VLE-PPT	1 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Cryolite - as F	VLE-PPT	2.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Calcium fluoride - as F	VLE-PPT	2.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Titanium dioxide (naturally occurring)	VLE-PPT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Iron - as Fe	VLE-PPT	1 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Manganese - as Mn	VLE-PPT	0.2 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Potassium hydroxide	VLE-P	2 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Tin	VLE-PPT	2 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)



Tungeton on W	LVI F CT	10 m a/m2	Maying OFLa (NOM 040 STDS 2014
Tungsten - as W	VLE-CT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended
			(04 2014)
	VLE-PPT	5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Copper and/or copper alloys and compounds (as Cu) - Fume as Cu	VLE-PPT	0.2 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Copper and/or copper alloys and compounds (as Cu) - Dust and mist as Cu	VLE-PPT	1 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Aluminum and/or aluminum alloys (as Al) - Respirable fraction.	VLE-PPT	1 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Silicon - Inhalable fraction.	VLE-PPT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Silicon - Respirable fraction.	VLE-PPT	3 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Silicon dioxide (amorphous) - Inhalable fraction.	VLE-PPT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Silicon dioxide (amorphous) - Respirable fraction.	VLE-PPT	3 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Magnesite - Respirable fraction.	VLE-PPT	3 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Magnesite - Inhalable fraction.	VLE-PPT	10 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Quartz - Respirable fraction.	VLE-PPT	0.025 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Cobalt and compounds (as Co) - as Co	VLE-PPT	0.02 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Iron oxide - Respirable fraction.	VLE-PPT	5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)

Biological Limit Values: US

Chemical Identity	Exposure Limit Values	Source
Nickel (Nickel: Sampling time: End of shift at end of work week.)	5 μg/l (Urine)	ACGIH BEI (01 2021)
Chromium and chromium alloys or compounds (as Cr) (Total chromium: Sampling time: End of shift at end of work week.)	0.7 μg/l (Urine)	ACGIH BEI (01 2021)
Cryolite (Fluoride: Sampling time: Prior to shift.)	2 mg/l (Urine)	ACGIH BEI (03 2013)
Cryolite (Fluoride: Sampling	3 mg/l (Urine)	ACGIH BEI (03 2013)



time: End of shift.)		
Calcium fluoride (Fluoride:	2 mg/l (Urine)	ACGIH BEI (03 2013)
Sampling time: Prior to shift.)		
Calcium fluoride (Fluoride:	3 mg/l (Urine)	ACGIH BEI (03 2013)
Sampling time: End of shift.)		
Cobalt and compounds (as	15 μg/l (Urine)	ACGIH BEI (03 2015)
Co) (Cobalt: Sampling time:		
End of shift at end of work		
week.)		

Biological Limit Values: Mexico

Chemical Identity	Exposure Limit Values	Source
Cryolite (fluorides: Sampling time: End of shift.)	10 mg/g (Creatinine in urine)	MX IBE (06 2012)
Cryolite (fluorides: Sampling time: Prior to shift.)	3 mg/g (Creatinine in urine)	MX IBE (06 2012)
Calcium fluoride (fluorides: Sampling time: End of shift.)	10 mg/g (Creatinine in urine)	MX IBE (06 2012)
Calcium fluoride (fluorides: Sampling time: Prior to shift.)	3 mg/g (Creatinine in urine)	MX IBE (06 2012)
Cobalt and compounds (as Co) (Cobalt: Sampling time: End of shift at end of work week.)	15 μg/l (Urine)	MX IBE (06 2012)
	1 μg/l (Blood)	MX IBE (06 2012)

Additional exposure limits under the conditions of use: US

Chemical Identity	Туре	Exposure Limit Values		Source
Carbon dioxide	TWA	5,000 ppm		US. ACGIH Threshold Limit Values (12 2010)
	STEL	30,000 ppm		US. ACGIH Threshold Limit Values (12 2010)
	PEL	5,000 ppm	9,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	30,000 ppm	54,000 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	REL	5,000 ppm	9,000 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	IDLH	40,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Carbon monoxide	TWA	25 ppm		US. ACGIH Threshold Limit Values (12 2010)
	PEL	50 ppm	55 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	35 ppm	40 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	Ceil_Time	200 ppm	229 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	IDLH	1,200 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Nitrogen dioxide	TWA	0.2 ppm		US. ACGIH Threshold Limit Values (02 2012)
	Ceiling	5 ppm	9 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	1 ppm	1.8 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	IDLH	20 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
	IDLH	13 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Ozone	PEL	0.1 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



	Ceil_Time	0.1 ppm	0.2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	TWA	0.05 ppm		US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.10 ppm		US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.08 ppm		US. ACGIH Threshold Limit Values (03 2014)
	IDLH	5 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
	TWA	0.20 ppm		US. ACGIH Threshold Limit Values (02
Manganese - Fume as Mn	Ceiling		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02
	REL		1 mg/m3	2006) US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL		3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Manganese - Inhalable fraction as Mn	TWA		0.1 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Manganese - Respirable fraction as Mn	TWA		0.02 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Manganese	IDLH		500 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Chromium (VI)	TWA		0.005 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_AC T		0.0025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	Ceiling		0.1 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000 (02 2006)
Chromium (VI) - as Cr(VI)	REL		0.0002 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Chromium (VI) - Inhalable fraction as Cr(VI)	TWA		0.0002 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
nuonem de ex(v)	TWA		0.0002 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
	STEL		0.0005 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
	STEL		0.0005 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
Chromium (VI)	IDLH		15 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (2018)
Nickel - Inhalable fraction.	TWA		1.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Nickel - as Ni	REL		0.015 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Nickel	IDLH		10 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
Nickel - as Ni	PEL		1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Chromium oxide - as Cr	PEL		0.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Chromium oxide - Inhalable fraction as Cr(III)	TWA		0.003 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
Chromium oxide - as Cr(III)	REL		0.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Chromium oxide	IDLH		25 mg/m3	US. NIOSH. Immediately Dangerous to
Chromium oxide - Inhalable	TWA		0.003 mg/m3	Life or Health (IDLH) Values (10 2017) US. ACGIH Threshold Limit Values (01 2021)
fraction as Cr(III) Fluorides (as F) - as F	TWA		2.5 mg/m3	US. ACGIH Threshold Limit Values (12
	PEL		2.5 mg/m3	2010) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



Fluorides (as F) - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
Fluorides (as F)	IDLH	250 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)

Chemical Identity Carbon dioxide	Туре	Exposure Li	mit Values	Source
	STEL	30,000 ppm	54,000 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	5,000 ppm	9,000 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	5,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	15,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5,000 ppm		Canada. Manitoba OELs (Reg. 217/2006 The Workplace Safety And Health Act), a amended (03 2011)
	STEL	30,000 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), a amended (03 2011)
	STEL	30,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	5,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	5,000 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	30,000 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	5,000 ppm	9,000 mg/m3	Canada. Quebec OELs. (Ministry of Labo - Regulation respecting occupational health and safety), as amended (09 2017
	STEL	30,000 ppm	54,000 mg/m3	Canada. Quebec OELs. (Ministry of Laboral - Regulation respecting occupational health and safety), as amended (09 2017
Carbon monoxide	TWA	25 ppm	29 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. Manitoba OELs (Reg. 217/2006 The Workplace Safety And Health Act), a amended (03 2011)



	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (07 2010)
	8 HR ACL	25 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	190 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	35 ppm	40 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	200 ppm	230 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Nitrogen dioxide	STEL	5 ppm	9.4 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	3 ppm	5.6 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	CEILING	1 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.2 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2012)
	STEL	5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	3 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	3 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	5 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	3 ppm	5.6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Ozone	STEL	0.3 ppm	0.6 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.1 ppm	0.2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.05 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.08 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07



		_		2007)
	TWA	0.2 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 ppm	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (07 2010)
	STEL	0.3 ppm	0.6 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (07 2010)
	15 MIN ACL	0.15 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	8 HR ACL	0.05 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	CEILING	0.1 ppm	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (12 2008)
	TWA	0.05 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
	TWA	0.08 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
	TWA	0.10 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
	TWA	0.20 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (02 2020)
Manganese - as Mn	TWA		0.2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	8 HR ACL		0.2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL		0.6 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Manganese - Respirable fraction as Mn	TWA		0.02 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
Manganese - Inhalable fraction as Mn	TWA		0.1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2014)
Manganese - as Mn	TWA		0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Manganese - Fume, total dust as Mn	TWA		0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Manganese - Respirable as Mn	TWA		0.02 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Manganese - Total - as Mn	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)



Chromium (VI) - as Cr	TWA	0.01 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.05 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.05 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	15 MIN ACL	0.03 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	0.15 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	8 HR ACL	0.01 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	8 HR ACL	0.05 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	0.05 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.01 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Chromium (VI) - Inhalable fraction as Cr(VI)	STEL	0.0005 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
	STEL	0.0005 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
	TWA	0.0002 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
	TWA	0.0002 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
Chromium (VI) - Total - as Cr	CEILING	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Nickel	TWA	1.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Nickel - as Ni	TWA	0.05 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Nickel - Inhalable fraction as Ni	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	8 HR ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety



			Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Nickel - Inhalable dust.	TWA	1.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Chromium oxide - as Cr	TWA	0.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	0.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	0.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Chromium oxide - Inhalable fraction as Cr(III)	TWA	0.003 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
Chromium oxide - Total - as Cr	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Chromium oxide - Inhalable fraction as Cr(III)	TWA	0.003 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (01 2021)
Fluorides (as F) - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	TWA	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Additional exposure limits under the conditions of use: Mexico



Chemical Identity	Туре	Exposure Limit Values	Source
Carbon dioxide	VLE-CT	30,000 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
	VLE-PPT	5,000 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Carbon monoxide	VLE-PPT	25 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Nitrogen dioxide	VLE-PPT	0.2 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Ozone	VLE-P	0.1 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Manganese - as Mn	VLE-PPT	0.2 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Chromium (VI)	VLE-PPT	0.05 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Nickel - Inhalable fraction as Ni	VLE-PPT	1.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Chromium oxide	VLE-PPT	0.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Fluorides (as F) - as F	VLE-PPT	2.5 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)

Appropriate Engineering Controls

Ventilation: Use enough ventilation and local exhaust at the arc, flame or heat source to keep the fumes and gases from the worker's breathing zone and the general area. Train the operator to keep their head out of the fumes. **Keep exposure as low as possible.**

Individual protection measures, such as personal protective equipment General information: Exposure Guidelines: To reduce the po

Exposure Guidelines: To reduce the potential for overexposure, use controls such as adequate ventilation and personal protective equipment (PPE). Overexposure refers to exceeding applicable local limits, the American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values (TLVs) or the Occupational Safety and Health Administration's (OSHA) Permissible Exposure Limits (PELs). Workplace exposure levels should be established by competent industrial hygiene assessments. Unless exposure levels are confirmed to be below the applicable local limit, TLV or PEL, whichever is lower, respirator use is required. Absent these controls, overexposure to one or more compound constituents, including those in the fume or airborne particles, may occur resulting in potential health hazards. According to the ACGIH, TLVs and Biological Exposure Indices (BEIs) "represent conditions under which ACGIH believes that nearly all workers may be repeatedly exposed without adverse health effects." The ACGIH further states that the TLV-TWA should be used as a guide in the control of health hazards and should not be used to indicate a fine line between safe and dangerous exposures. See Section





10 for information on constituents which have some potential to present health hazards. Welding consumables and materials being joined may contain chromium as an unintended trace element. Materials that contain chromium may produce some amount of hexavalent chromium (CrVI) and other chromium compounds as a byproduct in the fume. In 2018, the American Conference of Governmental Industrial Hygienists (ACGIH) lowered the Threshold Limit Value (TLV) for hexavalent chromium from 50 micrograms per cubic meter of air (50 µg/m³) to 0.2 µg/m³. At these new limits, CrVI exposures at or above the TLV may be possible in cases where adequate ventilation is not provided. CrVI compounds are on the IARC and NTP lists as posing a lung cancer and sinus cancer risk. Workplace conditions are unique and welding fume exposures levels vary. Workplace exposure assessments must be conducted by a qualified professional, such as an industrial hygienist, to determine if exposures are below applicable limits and to make recommendations when necessary for preventing overexposures.

Eye/face protection:

Wear helmet or use face shield with filter lens shade number 12 or darker for open arc processes – or follow the recommendations as specified in ANSI Z49.1, Section 4, based on your process and settings. No specific lens shade recommendation for submerged arc or electroslag processes. Shield others by providing appropriate screens and flash goggles.

Skin Protection
Hand Protection:

Wear protective gloves. Suitable gloves can be recommended by the glove

supplier.

Other:

Protective Clothing: Wear hand, head, and body protection which help to prevent injury from radiation, open flames, hot surfaces, sparks and electrical shock. See Z49.1. At a minimum, this includes welder's gloves and a protective face shield when welding, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing when welding, brazing and soldering. Wear dry gloves free of holes or split seams. Train the operator not to permit electrically live parts or electrodes from contacting the skin . . . or clothing or gloves if they are wet. Insulate yourself from the work piece and ground using dry plywood, rubber mats or other dry insulation.

Respiratory Protection:

Keep your head out of fumes. Use enough ventilation and local exhaust to keep fumes and gases from your breathing zone and the general area. An approved respirator should be used unless exposure assessments are below applicable exposure limits.

Hygiene measures:

Do not eat, drink or smoke when using the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.2, F1.3 and F1.5, available from the American Welding Society, www.aws.org.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Steel rod with extruded flux coating.

Physical state: Solid Form: Solid





Color:

Odor:

No data available.

range:

Flash Point: No data available. **Evaporation rate:** No data available. Flammability (solid, gas): No data available. Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): No data available. Flammability limit - lower (%): No data available. **Explosive limit - upper:** No data available. **Explosive limit - lower:** No data available. Vapor pressure: No data available. Vapor density: No data available. Density: No data available.

Relative density: Solubility(ies)

Solubility in water: No data available.

Solubility (other): No data available.

Partition coefficient (n- No data available.

octanol/water):

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. STABILITY AND REACTIVITY

Reactivity: The product is non-reactive under normal conditions of use, storage and

transport.

No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Strong acids. Strong oxidizing substances. Strong bases.

Hazardous Decomposition

Products:

Fumes and gases from welding and its allied processes such as brazing and soldering cannot be classified simply. The composition and quantity of both are dependent upon the metal to which the joining or hot work is applied, the process, procedure - and where applicable - the electrode or consumable used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded or worked (such as paint, plating, or galvanizing), the number of operators and the volume of the work area, the quality and amount of ventilation, the position of the operator's head with respect to the fume plume, as well as the presence of



contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities.)

In cases where an electrode or other applied material is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc., as noted above. Reasonably expected fume constituents produced during arc welding and brazing include the oxides of iron, manganese and other metals present in the welding consumable or base metal. Hexavalent chromium compounds may be in the welding or brazing fume of consumables or base metals which contain chromium. Gaseous and particulate fluoride may be in the fume of consumables or flux materials which contain fluoride. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc associated with welding.

11. TOXICOLOGICAL INFORMATION

General information: The International Agency for Research on Cancer (IARC) has determined

welding fumes and ultraviolet radiation from welding are carcinogenic to humans (Group 1). According to IARC, welding fumes cause cancer of the lung and positive associations have been observed with cancer of the kidney. Also according to IARC, ultraviolet radiation from welding causes ocular melanoma. IARC identifies gouging, brazing, carbon arc or plasma arc cutting, and soldering as processes closely related to welding. Read and understand the manufacturer's instructions, Safety Data Sheets and

the precautionary labels before using this product.

Information on likely routes of exposure

Inhalation: Potential chronic health hazards related to the use of welding consumables

are most applicable to the inhalation route of exposure. Refer to Inhalation

statements in Section 11.

Skin Contact: Arc rays can burn skin. Skin cancer has been reported.

Eye contact: Arc rays can injure eyes.

Ingestion: Health injuries from ingestion are not known or expected under normal use.

Symptoms related to the physical, chemical and toxicological characteristics



Inhalation:

Respiratory exposure to the crystalline silica present in this welding electrode is not anticipated during normal use. Respiratory overexposure to airborne crystalline silica is known to cause silicosis, a form of disabling pulmonary fibrosis which can be progressive and may lead to death. Crystalline silica is on the IARC (International Agency for Research on Cancer) and NTP (National Toxicology Program) lists as posing a cancer risk to humans. Note: All regional authorities do not use the same criteria for assigning carcinogenic classifications to chemicals. For example, the European Union (EU) CLP does not require classifying crystalline silica as a carcinogenic compound. Short-term (acute) overexposure to fumes and gases from welding and allied processes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long-term (chronic) overexposure to fumes and gases from welding and allied processes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified

Specified substance(s):

Limestone LD 50 (Rat): 6,450 mg/kg
Calcium fluoride LD 50 (Rat): 4,250 mg/kg
Sodium silicate LD 50 (Rat): 1.1 g/kg
Iron LD 50 (Rat): 98.6 g/kg
Potassium hydroxide LD 50 (Rat): 333 mg/kg
Copper and/or copper LD 50 (Rat): 481 mg/kg

alloys and compounds

(as Cu)

Potassium carbonate LD 50 (Rat): 1,870 mg/kg Cobalt and compounds LD 50 (Rat): 550 mg/kg

(as Co)

Dermal

Product: Not classified

Specified substance(s):

Potassium carbonate LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: Not classified

Specified substance(s):

Aluminum and/or LC 50 (Rat, 1 h): 7.6 mg/l

aluminum alloys (as Al)

Cobalt and compounds LC 50 (Rat, 4 h): <= 0.05 mg/l

(as Co)

Repeated dose toxicity

Product: Not classified

Skin Corrosion/Irritation

Product: Not classified

Serious Eye Damage/Eye Irritation

Product: Not classified

Respiratory or Skin Sensitization

Product: Not classified





Carcinogenicity

Product: Arc rays: Skin cancer has been reported.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Nickel Overall evaluation: 2B. Possibly carcinogenic to humans. Titanium dioxide Overall evaluation: 2B. Possibly carcinogenic to humans.

(synthetic)

Overall evaluation: 2B. Possibly carcinogenic to humans.

(naturally occurring)

Quartz Overall evaluation: 1. Carcinogenic to humans.

Cobalt and Overall evaluation: 2B. Possibly carcinogenic to humans.

compounds (as Co)

US. National Toxicology Program (NTP) Report on Carcinogens:

Nickel Reasonably Anticipated to be a Human Carcinogen.

Quartz Known To Be Human Carcinogen.

Cobalt and Reasonably Anticipated to be a Human Carcinogen.

compounds (as Co)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

Quartz Cancer

Germ Cell Mutagenicity

In vitro

Product: Not classified

In vivo

Product: Not classified

Reproductive toxicity

Product: Not classified

Specific Target Organ Toxicity - Single Exposure

Product: Not classified

Specific Target Organ Toxicity - Repeated Exposure

Product: Not classified

Aspiration Hazard

Product: Not classified

Other effects: Organic polymers may be used in the manufacture of various welding

consumables. Overexposure to their decomposition byproducts may result in a condition known as polymer fume fever. Polymer fume fever usually occurs within 4 to 8 hours of exposure with the presentation of flu like symptoms, including mild pulmonary irritation with or without an increase in body temperature. Signs of exposure can include an increase in white blood cell count. Resolution of symptoms typically occurs quickly, usually

not lasting longer than 48 hours.

Symptoms related to the physical, chemical and toxicological characteristics under the condition of use

Inhalation:

Specified substance(s):

Manganese Overexposure to manganese fumes may affect the brain and central

nervous system, resulting in poor coordination, difficulty speaking, and arm

or leg tremor. This condition can be irreversible.



Chromium (VI) Chromates may cause ulceration, perforation of the nasal septum, and

severe irritation of the bronchial tubes and lungs. Liver damage and allergic reactions, including skin rash, have been reported. Asthma has been reported in some sensitized individuals. Skin contact may result in irritation, ulceration, sensitization, and contact dermatitis. Chromates contain the hexavalent form of chromium. Hexavalent chromium and its compounds are on the IARC (International Agency for Research on Cancer) and NTP (National Toxicology Program) lists as posing a cancer

risk to humans.

Nickel Nickel and its compounds are on the IARC and NTP lists as posing

respiratory cancer risk, and are skin sensitizers with symptoms ranging

from slight itch to severe dermatitis.

Additional toxicological Information under the conditions of use:

Acute toxicity

Oral

Specified substance(s):

Chromium (VI) LD 50 (Rat): 27 - 59 mg/kg Fluorides (as F) LD 50 (Rat): 4,250 mg/kg

Inhalation

Specified substance(s):

Carbon dioxide LC Lo (Human, 5 min): 90000 ppm

Carbon monoxide

Nitrogen dioxide
Ozone

Chromium (VI)

LC 50 (Rat, 4 h): 1300 ppm

LC 50 (Rat, 4 h): 88 ppm

LC Lo (Human, 30 min): 50 ppm

LC 50 (Rat, 4 h): 33 - 70 mg/m3

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Specified substance(s):

Chromium (VI) Overall evaluation: 1. Carcinogenic to humans.

Nickel Overall evaluation: 2B. Possibly carcinogenic to humans.

Chromium oxide Overall evaluation: 3. Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Specified substance(s):

Chromium (VI) Known To Be Human Carcinogen.

Nickel Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

Specified substance(s):

Chromium (VI) Cancer

Other effects:

Specified substance(s):

Carbon dioxide Asphyxia

Carbon monoxide Carboxyhemoglobinemia
Nitrogen dioxide Lower respiratory tract irritation
Nickel Dermatitis Pneumoconiosis

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute hazards to the aquatic environment:

Fish

Product: Not classified.

Specified substance(s):



LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.916 mg/l Nickel

Molybdenum LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 800

mg/l

Cryolite LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 47

mg/l

LC 50 (96 h): 340 mg/l Calcium fluoride

Sodium silicate LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 1.800 mg/l

Potassium hydroxide LC 50 (Gambusia affinis, 96 h): 80 mg/l

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 1.277 - 3.649 mg/l Zinc **Bentonite** LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h):

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 1.6 mg/l

19.000 mg/l

Copper and/or copper

alloys and compounds

(as Cu)

Aluminum and/or LC 50 (Grass carp, white amur (Ctenopharyngodon idella), 96 h): 0.21 -

0.31 ma/l aluminum allovs (as AI)

Potassium carbonate LC 50 (Fathead minnow (Pimephales promelas), 96 h); < 750 mg/l Cobalt and compounds LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 28 d): >

(as Co) 0.17 - < 15.61 mg/l

Aquatic Invertebrates

Product: Not classified.

Specified substance(s):

Nickel EC 50 (Water flea (Daphnia magna), 48 h): 1 mg/l Calcium fluoride EC 50 (Daphnia magna; Daphnia sp., 48 h): 270 mg/l

EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 22.94 - 49.01 mg/l Sodium silicate

Manganese EC 50 (Water flea (Daphnia magna), 48 h): 40 mg/l Zinc EC 50 (Water flea (Daphnia magna), 48 h): 2.8 mg/l EC 50 (Water flea (Daphnia magna), 48 h): 0.102 mg/l Copper and/or copper

alloys and compounds

(as Cu)

Potassium carbonate LC 50 (Water flea (Ceriodaphnia dubia), 48 h): 580 - 670 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: Not classified.

Aquatic Invertebrates

Product: Not classified.

Toxicity to Aquatic Plants

Product: Not classified.

Specified substance(s):

Copper and/or copper alloys and compounds

(as Cu)

LC 50 (Green algae (Scenedesmus dimorphus), 3 d): 0.0623 mg/l

Persistence and Degradability

Biodegradation

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Nickel Zebra mussel (Dreissena polymorpha), Bioconcentration Factor (BCF):

5,000 - 10,000 (Lotic) Bioconcentration factor calculated using dry weight

tissue conc





Zinc Brown shrimp (Penaeus aztecus), Bioconcentration Factor (BCF): > 400 - <

600 (Static)

Copper and/or copper alloys and compounds

Blue-green algae (Anacystis nidulans), Bioconcentration Factor (BCF):

36.01 (Static)

(as Cu)
Cobalt and compounds

(as Co)

Brown shrimp (Penaeus aztecus), Bioconcentration Factor (BCF): > 2,250 -

< 2,500 (Static)

Mobility in soil: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized whenever

possible. When practical, recycle in an environmentally acceptable, regulatory compliant manner. Dispose of non-recyclable products in accordance with all applicable Federal, State, Provincial, and Local

requirements.

Disposal instructions: Disposal of this product may be regulated as a Hazardous Waste. The

welding consumable and/or by-product from the welding process (including, but not limited to slag, dust, etc.) may contain levels of leachable heavy metals such as Barium or Chromium. Prior to disposal, a representative

sample must be analyzed in accordance with US EPA's Toxicity

Characteristic Leaching Procedure (TCLP) to determine if any constituents exist above regulated threshold levels. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner

according to Federal, State and Local Regulations.

Contaminated Packaging: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

14. TRANSPORT INFORMATION

DOT

UN number or ID number:

UN Proper Shipping Name: NOT DG REGULATED

Transport Hazard Class(es)

Class: NR
Label(s): –
Packing Group: –
Marine Pollutant: No

IMDG

UN number or ID number:

UN Proper Shipping Name: NOT DG REGULATED

Transport Hazard Class(es)

Class: NR Label(s): –

EmS No.:

Packing Group: –
Marine Pollutant: No

IATA

UN number or ID number:

Proper Shipping Name: NOT DG REGULATED

Transport Hazard Class(es):





Class: NR
Label(s):
Packing Group: Marine Pollutant: No
Cargo aircraft only: Allowed.

TDG

UN number or ID number:

UN Proper Shipping Name: NOT DG REGULATED

Transport Hazard Class(es)

Class: NR
Label(s): –
Packing Group: –
Marine Pollutant: No

15. REGULATORY INFORMATION

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

 Chemical Identity
 OSHA hazard(s)

 Quartz
 kidney effects

lung effects

immune system effects

Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Nickel 100lbs. Chromium and chromium alloys or 5000lbs.

compounds (as Cr)

Manganese Included in the regulation but with no data values. See

regulation for further details.

Potassium hydroxide 1000lbs. Zinc 1000lbs. Copper and/or copper alloys and 5000lbs.

compounds (as Cu)

Cobalt and compounds (as Co) Included in the regulation but with no data values. See

regulation for further details.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Not classified Not classified

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity



SARA 313 (TRI Reporting)

Reporting threshold
Chemical IdentityReporting threshold for
for other usersReporting threshold for
manufacturing and processing

Nickel 10000 lbs 25000 lbs. Chromium and chromium alloys or 10000 lbs 25000 lbs.

compounds (as Cr)

Cobalt and compounds (as Co) 10000 lbs 25000 lbs.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity Reportable quantity

Potassium hydroxide Reportable quantity: 1000 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations US. California Proposition 65



WARNING: This product can expose you to chemicals including, Nickel, Titanium dioxide (synthetic), Titanium dioxide (naturally occurring), Quartz, Cobalt and compounds (as Co), which is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

WARNING: This product contains or produces a chemical known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code Section 25249.5 et seq.)

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act Chemical Identity

US. Massachusetts RTK - Substance List

Chemical Identity

Nickel

Chromium and chromium alloys or compounds (as Cr)

Quartz

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Nickel

Chromium and chromium alloys or compounds (as Cr)

Molybdenum

Titanium dioxide (synthetic)

Limestone

Cryolite

Calcium fluoride

Titanium dioxide (naturally occurring)

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Chemical Identity

Cryolite

Zinc



Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional

Reporting Requirements

NPRI PT5 Not Regulated

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)

NPRI Not Regulated

Greenhouse Gases

Not Regulated

Controlled Drugs and Substances Act

CA CDSI Not Regulated CA CDSII Not Regulated CA CDSIII Not Regulated **CA CDSIV** Not Regulated CA CDSV Not Regulated CA CDSVII Not Regulated **CA CDSVIII** Not Regulated

Precursor Control Regulations

Not Regulated

Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR): Not applicable

Inventory Status:

Canada DSL Inventory List: One or more components are not listed or are exempt from listing.

EINECS, ELINCS or NLP: On or in compliance with the inventory

One or more components are not listed or are exempt from listing. Japan (ENCS) List:

China Inv. Existing Chemical Substances: On or in compliance with the inventory On or in compliance with the inventory Korea Existing Chemicals Inv. (KECI):

Canada NDSL Inventory: One or more components are not listed or are exempt from listing. Philippines PICCS: One or more components are not listed or are exempt from listing.

New Zealand Inventory of Chemicals: On or in compliance with the inventory

Japan ISHL Listing: One or more components are not listed or are exempt from listing. Japan Pharmacopoeia Listing: One or more components are not listed or are exempt from listing. One or more components are not listed or are exempt from listing. Mexico INSQ: Ontario Inventory: One or more components are not listed or are exempt from listing.

Taiwan Chemical Substance Inventory: On or in compliance with the inventory

Australia Industrial Chem. Act (AIIC): One or more components are not listed or are exempt from listing.

US TSCA Inventory: On or in compliance with the inventory

Switzerland New Subs One or more components are not listed or are exempt from listing. Notified/Registered:

Thailand Existing Chemical Inv. List: One or more components are not listed or are exempt from listing. Vietnam National Chemical Inventory: One or more components are not listed or are exempt from listing.

16. OTHER INFORMATION

Definitions:

Revision Date: 04/25/2022



Further Information:

Additional information is available by request.

Disclaimer:

The Lincoln Electric Company urges each end user and recipient of this SDS to study it carefully. See also www.lincolnelectric.com/safety. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond Lincoln Electric's control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and local laws and regulations remain the responsibility of the user.

© 2022 Lincoln Global, Inc. All Rights Reserved.