

# SPIRIT® II 150

## FINELINE™ HIGH DEFINITION PLASMA CUTTING TECHNOLOGY



Spirit II 150 shown with Automatic Gas Console (AGC) configuration



### KEY FEATURES

The Spirit® II series plasma cutting power sources with FineLine™ High Definition Plasma Cutting Technology delivers the best cut quality in the industry. Our combination of patented processes, torch and consumable design ensures a precise gas flow that creates a consistent shape in the plasma arc.

Exceptional pierce, cut and marking capabilities, virtually dross free, with high definition edge quality of 2 degrees or less of a cut edge bevel

Designed to use up to 78% less plasma gas than the competition for lower operating costs

Robust design components with rigorous manufacturing and testing standards for exceptional product reliability and productivity

#### Processes »

Plasma Cutting and Marking

#### Output »

150A DC @ 100% Duty Cycle

#### Product Number »

See literature E15.17

#### Cutting Capacity

Type	Production Pierce	Max. Thickness Edge Start with Dross
Mild Steel	1.25 (32 mm)	1.50 in. (38 mm)

## OPERATING DATA

Mild Steel			
Amp	Thickness in. (mm)	Speed ipm (m/min.)	Gas
30	0.036 (1.0)	105 (2.615)	O <sub>2</sub> Plasma O <sub>2</sub> Shield
	0.075 (2.0)	65 (1.615)	
	0.135 (3.0)	40 (1.285)	
50	0.075 (2.0)	200 (4.885)	O <sub>2</sub> Plasma Air Shield
	0.125 (3.0)	180 (4.660)	
	1/4 (6.0)	75 (2.075)	
70	0.125 (3.0)	190 (4.995)	O <sub>2</sub> Plasma Air Shield
	1/4 (5.0)	120 (3.265)	
	3/8 (6.0)	75 (3.105)	
100	1/4 (6.0)	150 (3.950)	O <sub>2</sub> Plasma Air Shield
	1/2 (12.0)	65 (1.850)	
	3/4 (20.0)	35 (0.800)	
150	1/4 (6.0)	165 (4.305)	O <sub>2</sub> Plasma Air Shield
	1/2 (12.0)	90 (2.485)	
	1 (25.0)	40 (1.040)	
	1-1/4 (32.0)	25 (0.625)	
	1-1/2 (38.0)*	15 (0.385)	
Aluminum			
30	0.040 (1.0)	150 (3.885)	Air Plasma N <sub>2</sub> Shield
50	0.080 (2.0)	90 (2.360)	
70	0.080 (2.0)	250 (6.400)	
	3/16 (5.0)	80 (1.920)	
	1/2 (12.0)	30 (0.820)	
100	1/4 (6.0)	105 (2.710)	
	3/8 (10.0)	90 (2.210)	
	1/2 (12.0)	70 (1.890)	
150	1/4 (6.0)	145 (3.770)	
	1/2 (12.0)	90 (2.430)	
	3/4 (20.0)	45 (0.990)	

Stainless Steel			
Amp	Thickness in. (mm)	Speed ipm (m/min.)	Gas
30	0.036 (1.0)	200 (4.855)	Air Plasma Air Shield
	0.075 (2.0)	90 (3.260)	
50	0.075 (2.0)	105 (2.565)	Air Plasma N <sub>2</sub> Shield
	0.120 (3.0)	65 (1.685)	
70	1/4 (6.0)	40 (1.075)	
	0.135 (3.0)	120 (3.210)	
100	3/8 (6.0)	50 (2.050)	
	1/2 (12.0)	80 (1.935)	
150	1/2 (12.0)	55 (1.540)	
	1/4 (6.0)	150 (3.910)	
	3/4 (20.0)	85 (2.330)	
70	3/16 (5.0)	45 (1.030)	H17 Plasma N <sub>2</sub> Shield
	3/16 (5.0)	80 (2.030)	
100	1/4 (6.0)	100 (2.625)	
	1/2 (12.0)	60 (1.610)	
150	3/4 (20.0)	40 (0.940)	
	3/4 (20.0)	40 (0.940)	


\* Requires edge start or moving pierce

## CUT QUALITY OVER CONSUMABLE LIFE



### Spirit II 150 » 150A, 3/8 in. (10 mm) Mild Steel

Based on testing performed in lab conditions in 2014



#### CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company® is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to [www.lincolnelectric.com](http://www.lincolnelectric.com) for any updated information.

All trademarks and registered trademarks are the property of their respective owners.

**The Lincoln Electric Company**

4130 Carolina Commerce Parkway · Ladson, SC · 29456 · U.S.A.

Additional Locations: Europe, Asia Pacific and India

[www.lincolnelectric.com](http://www.lincolnelectric.com)