

# L-61

## CLASSIFICATION

AWS A5.17	EM12K	A-Nr	1
ISO 14171-A	S2Si	F-Nr	6
		9606 FM	1

## GENERAL DESCRIPTION

Industry standard for submerged arc welding applications  
 A low carbon, medium manganese, low silicon general purpose submerged arc wire  
 A good choice for a wide range of applications with single or multiple pass subarc welding

## APPROVALS

	ABS	TÜV	BV	DNV	GL	LRS	RINA	RMRS	CRS	PRS
761	X	X	X	X	X	X	X	X	X	X
780		X	X	X	X	X	X	X	X	X
8500					X					
888		X								
860	X	X	X	X	X	X	X	X	X	
P230	X	X				X	X			
781		X								

## CHEMICAL COMPOSITION (W%), TYPICAL, WIRE

C	Mn	Si
0.1	1.0	0.25

## PACKAGING AND AVAILABLE SIZES

Diameter (mm)	1.6	2.0	2.4	3.2	4.0	4.8
25 kg stein basket B415+VCI	X	X	X	X	X	X
100 kg stein basket B785		X	X	X	X	X
200 kg Speed Feed® Drum		X				
300 kg wooden reel		X	X	X	X	
350 kg Speed Feed® Drum	X	X				
400 kg Speed Feed® Drum			X	X	X	
600 kg Speed Feed® Drum			X		X	
600 kg Accutrak® Drum	X	X	X			
1000 kg Accutrak® Drum		X	X	X	X	
1000 kg coil liftable		X			X	