

# Speedtec® 405S Speedtec® 505S

## High output, reliable industrial machine

The Speedtec® range is the solution for Industrial Multi-process applications. With modular and compact design this welding set is easy to move around site. Transport is trouble free thanks to the lower weight of this new design. With the latest high frequency inverter technology, the arc is precisely controlled, many times faster than conventional analogue power sources. The welding characteristics of the welding power can be changed by software in real time updates.

A wide range of synergic programs are available as standard allowing simple yet precise control of welding parameters for the best results every time. The Speedtec® machines utilise the very latest power source technology for efficiency and lower energy consumption. Their advanced Inverter technology will save both time as well as energy. Driven by Lincoln Electric's Green Initiative, we aim to reduce the costs to you as well as the environment. These welding sets are available as 400A rated at 80% or 500A rated at 60% duty cycle (at 40°C). With the PF46 wire feed unit the welding set can support the MIG processes with synergic programs for Steel, Stainless Steel, Aluminium and Flux cored wires. Lift TIG and Stick functions are available as standard.

### Features

- Premium arc characteristic on CV MIG & Stick welding.
- Variable inductance control.
- Synergic capability.
- Job control with limits secured by a password (PF46).
- Continuous control of wire feed Speed and voltage.
- Remote control on the gun (PF46).
- Pre-setting (PF42) & Multi procedure (PF46).



### Processes

- MIG
- Flux-Cored
- Stick
- Lift TIG
- Gouging

### Recommended Consumables

- **Steel**  
Ultramag®
- **Flux-cored**  
Innershield® NR211-MP, Outershield® MC710-H, 71E-H, LW-71
- **Stainless steel**  
Lincoln 304L, 316L, 309LSi
- **Aluminium**  
SuperGlaze®

### Basic Unit Includes

- Primary cable 5 m
- Ground cable with clamp 3 m

### Recommended Packages Include

- PF4X wire feeder
- Speedtec® power source
- COOL ARC® 46 for water cooled version
- Cart
- 5 m-Interconnection cable, MIG gun and gas regulator

### Key Options

- K14105-1 Water cooler COOL ARC® 46
- K10349-PG(W)-xM Interconnection cables
- K10413-36-4M Linc gun 360G-300A 4m
- K10429-505-xM MIG gun LGS 505 W-450A-4/5m
- K14096-1 Cart Speedtec
- K10420-1 Coolant Acorox (2x5l)
- K14130-1 LACI (Lincoln Arlink Communication Interface)
- KP10519-8 TIG Torch Adaptor
- LE250-RG002 Gas flow regulator



### Technical Specifications

Product	Item Number	Primary Voltage (50-60Hz)	Current Range (A)	Rated Output	Fuse Type rG or Circuit Breaker Type Z	Weight (kg)	Dimensions HxWxD (mm)	Protection Class
Speedtec® 405S	K14117-1	400V/3Ph	20-400A	400A/34V/80%	32A	50	535x300x635	IP23
Speedtec® 505S	K14116-1		20-500A	500A/39V/60%	32A			

### Technical Specifications of Wire Feeders

Product	Item Number	Drive Roll	Cooling	Input Power	Output Power	WFS Range (m/min)	Wire Size Range (mm)		Weight (kg)	Dimensions HxWxD (mm)
							Solid	Cored		
PF-42	K14107-1	4	A/W	40V DC	500A@60%	1.0-22	0.8-1.6	1.0-1.6	18	460 x 300 x 640
PF-46	K14109-1						18.5			