

Vantage® 400 CE

Vantage® 500 CE

Compact, multi-process, excellent value

The Vantage® 400 CE and 500 CE are one of the most compact and powerful engine-driven welders / generators in the construction, pipe or rental fleet market today. They are also the most quiet with a smooth running 4-cylinder Perkins® water-cooled diesel engines. Use these multi-process welders for Stick welding with a large variety of electrodes, lift TIG welding, CV welding with shielding gas or Innershield wires and arc gouge up to 8 mm carbons for Vantage 400 and 10 mm carbons for Vantage 500. You will value the superior arc performance delivered by exclusive Lincoln Chopper Technology. You will also appreciate VRD™ (Voltage Reduction Device™) which reduces OCV (open circuit voltage) in the CC-Stick weld mode for added safety.

Features

- Compact case with stainless steel enclosure.
- Arc gouging up 8 mm.
- Downhill pipe welding mode. Excellent for cellulosic electrodes.
- Built-in "Hot Start" for easier starts and restrikes.
- Plenty of AC 50 Hz generator power: 3-phase 400V / 1 phase 220V / 1 phase 115V.
- Reliable Four-Cylinder Engine, water cooled, 1500 rpm Perkins Diesel engine.
- Innovative Service Access.
- Stainless steel enclosure delivers added protection and durability.
- Low noise to fit with European norms.



Processes

- Stick
- TIG
- MIG
- Flux-Cored
- Gouging

Key Options

- **KIT-400A-70-5M** Cable Kit 400A - 70 mm² - 5 m
- **GRD-400A-70-xM** Ground cable 400A - 70 mm² - 5/10/15 m
- **E/H-400A-70-xM** Electrode holder, 400A - 70 mm² - 5/10 m
- **K10376** Adapter M14/Dinse(F)
- **K10095-1-15M** Remote control - 15 m
- **K903-1** Spark Arrestor Kit
- **K2636-1** Medium Two-Wheel Trailer & Duo-Hitch® Ball/Eye Hitch
- **K2641-2** Four-Wheel Yard Trailer with Duo-Hitch® Ball/Eye Hitch



Technical Specifications

Product	Item Number	Current Range (A)	Rated Output	Type of Engine	Cylinders	Operation Speeds (rpm)	Weight (kg)	Dimensions HxWxD (mm)
Vantage® 400	K2502-3	30-400	350A/34V/100% 400A/30V/60%	Perkins 404D-22 Diesel	4	Full load: 1500 Low idle: 1200	560	913 x 642 x 1524
Vantage® 500	K2503-3	30-500	400A/36V/100% 450A/38V/60%	Perkins 404D-22 TURBO Diesel				

