

CROSS COUNTRY® 300

A Diesel-Powered Welder For Professional Pipeline Welders

It's All About the Arc

- Tuned by pipeline welders for pipeline welders
- Excellent for root, fill and cap passes
- Designed for cellulosic or low hydrogen stick electrodes

The Size is Right

- Easily fits on trucks
- Small footprint saves space in your truck bed
- Low height for clear visibility through your back window

Easy To Use

- Dual controls are designed for pipeline welding
- Fewer controls improves simplicity and reliability
- Easy access for routine maintenance, even when in a truck
- Start engine and change settings from hundreds of feet away with wireless remote

Flexible

- Supports DC stick, wire and TIG processes
- Easily connects to Lincoln wire feeders
- Powerful generator for grinders, pumps and travel trailers



Shown
K4166-1

Shown
K4166-3

Processes

Stick, Flux-Cored, MIG, TIG

Output



Input



Applications

- Cross country pipe
- Process piping
- Repair on pipe
- Maintenance jobs

Product Highlights

- Choose 125 ft. (38.1 m) wired remote or multi-function wireless remote control
- Up to 11kW/3Ph generator power
- Engine block heater
- Easy access battery jump studs
- Powder-coated steel enclosure
- Digital meters
- Polished stainless exhaust stack
- Sliding door engine access on both sides

Key Accessories

- Cold weather kit
- LN-25 Pipe portable wire feeder
- 125 ft. (38.1 m) Remote output control with 115V AC Receptacles

CROSS COUNTRY® 300 - SPECIFICATIONS

| Product Number | Engine | Rated Output Current /Voltage/Duty Cycle | AC Generator Power Output | Capacities | Dimensions H x W x L in (mm) | Weight lb (kg) |
|--|---|--|-------------------------------------|--|--|-------------------|
| K4166-1 Gray Painted Steel Case | 22 hp, 4 cylinder Kubota® V1505, Liquid-Cooled, Tier 4 Final | DC Pipe Current: 300A/32V/100% Range: 40 to 300 AMPS | Single Phase: 10kW Continuous | Fuel: 11.6 US gal (43.9 L) Oil: 6.4 qts (6.0 L) Coolant: 7.2 qts (6.8 L) | 31.9 x 25.3 x 56 (810 x 643 x 1422) | 1034 (469) |
| K4166-2 Gray Painted Steel Case w/Factory- Installed Wireless Remote | | DC Touch Start TIG® 250A/30V/100% Range: 20-250 Amps | Three Phase: 11 kW Continuous | | | |
| K4166-3 Stainless Steel Case w/Factory-Installed Wireless Remote | | DC Constant Voltage 300A/32V/100% 350A/28V/100% Range: 14-32 Volts Single Dial Continuous Control | | | | |
| K4166-7 Gray Painted Steel Case w/125 foot (38.1 m) Wired Remote One-Pak® Pkg | | | | | | |

CUSTOMER ASSISTANCE POLICY

The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.