

APEX 30M MECHANIZED CONTROLLER

MECHANIZED CONTROL WITH A CONVENIENT BUILT-IN WIRE FEEDER



PORTABLE ORBITAL WELDING

The APEX® 30M controllers offer the power of synchronizing amps, volts, travel speed and oscillation combined with powerful wire-feeding performance. Part of the APEX 3 Series platform of control systems, it is designed with the patented MAXTRAC® Wire Drive System, delivering the wire-feeding results you need for maximizing mechanized welding productivity and quality. The APEX 30M controller is engineered primarily for GMAW / FCAW processes, but it can also be configured for GTAW processes. Moving from flat track, plate or other structural beams to an orbital track takes only a simple weld head adjustment.

The APEX 30M suitcase-style controller incorporates a covered area housing, a robotic wire feeder and a spool holder, allowing for quick and easy setup in the shop or in the field. Weighing less than 50 lbs. (23 kg) with a convenient handle on top, it's as mobile as it is functional. Built as part of a digital platform geared towards reducing product obsolescence, the APEX 30M controller is designed for a longer service life as future enhancements to welding technologies become available.

Processes »

MIG, Pulsed MIG, Flux-Cored, GMAW- STT®

Applications »

Structural, Maritime, Power Generation, Pipeline, Process Piping, Construction

Input »



Output »



Product Numbers »

See the next page for complete specs

FEATURES

- » **Industry-Proven Performance** – Patented MAXTRAC® 4-roll wire drive system delivers powerful and dependable wire feeding.
- » **Best in Class Torque** – Reliable feeding in high-speed applications or long conduit runs.
- » **Precise Speed Control** – High-resolution tachometer for precise forward and reverse wire feed speed control.
- » **Optimized Design** – Complete wire drive and mechanized controller maximizes portability.
- » **Durable and Rugged** – Heavy-duty wire drive system engineered to withstand demanding mechanized applications with hinged cover for extra protection.
- » **Hassle-Free Maintenance** – Toolless design for drive roll, wire guide or pressure arm adjustments.

KEY CONTROLS



At the center of the APEX 30M Controller is the rugged and dependable MAXTRAC® 4-roll wire drive system that delivers industry-proven performance and reliability for even the most demanding welding applications.

- 1. Patented Split Wire Guides**
 - Full support for wire throughout the drive path
 - Minimized feeding problems
 - Removable out wire guide for easy access
 - No tools required
- 2. Patented Dual Spring Pressure Arm**
 - Easy turn numeric tension indicator
 - Set heavy tension for solid steel and stainless steel wire
 - Set moderate tension for cored wires
 - Set soft tension for aluminum wire
 - Wide idler arm hinge delivers improved drive roll clamping pressure
- 3. Twist-Lock Drive Roll Hubs**
 - Four gear-driven rolls
 - Fast, toolless changeovers
- 4. Rigid Cast Aluminum Frame**
 - Enhances precise drive roll alignment
- 5. Separate Drive Gear**
 - Reduces pressure on motor for extended service life
- 6. Patented Drive Rolls**
 - For steel – new design delivers 20% more feeding force
 - For aluminum – chrome-plated to resist build-up



PRODUCT SPECIFICATIONS

Product Name	Product Number	Input Power	Input Current	Output Power	Rated Output Current / Duty Cycle	Wire Feed Speed Range ipm (cm/min)	Wire Spool Size lb. (kg)	Dimensions L x W x H	Net Weight
APEX 30M Controller	K52160-1	40 VDC	10A Max	24 VDC	500A / 60% 450A / 100%	30-1200 (76-3048)	10-33 (4.5 - 15)	14.4 x 11.0 x 25.4 in 366 x 279 x 645 mm	49 (22)

OPTIONS

Description	Wire Size in. (mm)	Product Number
Solid Steel Wire, Smooth V Groove	.023-.030 (0.6-0.8)	KP1505-030S
	.035 (0.9)	KP1505-035S
	.040 (1.0)	KP1505-040S
	.040-.045 (1.0-1.2)	KP1505-045S
	.052 (1.4)	KP1505-052S
	1/16 (1.6)	KP1505-1/16S
Cored Steel Wire, Knurled V Groove	.030-.035 (0.8-0.9)	KP1505-035C
	.040-.045 (1.0-1.2)	KP1505-045C
	.052 (1.4)	KP1505-052C
	1/16 (1.6)	KP1505-1/16C
Cored or Solid Steel Wire, Knurled V Groove	.068-.072 (1.8)	KP1505-068
	5/64 (2.0)	KP1505-5/64
Aluminum Wire, Smooth U Groove	.035 (0.9)	KP1507-035A
	.040 (1.0)	KP1507-040A
	3/64 (1.2)	KP1507-3/64A
	1/16 (1.6)	KP1507-1/16A



CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.



The Lincoln Electric Company
22801 St. Clair Avenue · Cleveland, OH · 44117-1199 · U.S.A.

www.lincolnelectric.com